



SKYCABLE 8-PSK/PAL CI TWIN

Umsetzer-Karte für 2 digitale Sat-Programme im MPEG-2 Standard, in 2 analoge PAL-Programme

EAN	Art.-Nr.	Farbe	Gewicht (Karton)	Gewicht (Gerät)	Karton (BxHxT)	Gerät (BxHxT)
4019588059627	0000/5962	grün	1.1 kg	800 g	63.00 x 28.30 x 35.30 cm	3.50 x 23.70 x 24.00 cm

DECODER	Outer coding (BCH): GF(2 ¹⁶), t=8, 10, 12	Rauschen: ≤ 45 dB μ V typisch
Audiodecoder: MPEG1, MPEG2	TUNER (DVB-S)	Harmonische Produkte: ≤ -50 dB typisch
Videodecoder: MPEG2, MP@ML	DVB-S Demodulator: EN 300 421	Ausgangsfrequenz: 100 ... 860 MHz
TUNER (DVB-S2)	Demodulation: QPSK	Ausgangspegel: 81 ... 90 dB
DVB-S2 Demodulator: EN 302 307	Symbolraten: 2 ... 45 Mbaud	RF-MODULATOR
Demodulation: 8PSK, QPSK	FEC Code rate: 1/2, 2/4, 3/4, 5/6, 6/7, 7/8 (automatisch)	Modulation: CCIR PAL B/G
Roll off factor: 0,20; 0,25; 0,35	Interleaving: Convolutional; l=12	LIEFERUMFANG
FEC Block Size: 64 kB	Outer coding: Reed Solomon 204, 188, T=8	SkyCable 8PSK/PAL CI TWIN Karte
FEC Code rate (LDPC): 1/4, 1/3, 2/5, 1/2, 3/5, 2/3, 3/4, 4/5, 5/6, 8/9, 9/10	RF-AUSGANGSUMSETZER	
	C/N: 55 dB typisch	