



SCR-LNB

SCR-LNB with 2 legacy outputs

EAN	Colour	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
4019588178861	beige	0017/8886	344 g	292 g	14.50 x 6.00 x 11.50 cm	12.30 x 6.50 x 15.00 cm

TOP FEATURES

4 Receiver mit SCR-Unterstützung
anschließbar

2 Receiver über Legacy-Ausgang
anschließbar

SCR-Protokoll gemäß EN 50494

Wetterschutzgehäuse

Feed-ø 40 mm

LOCAL OSCILLATOR

Low band : 9.75 GHz

High band : 10.6 GHz

Accuracy : ± 1 MHz

Temperature drift : ± 3 MHz

Phase noise : -80 @10kHz

LNB CONTROL

Vertical : 11,5 ... 14 V

Horizontal : 16 ... 19 V

Band switch : 22 kHz

DiSEqC : 1.0

AMBIENT OPERATING CONDITIONS

Ambient temperature : -30 ... 60 °C

INPUT FREQUENCY RANGE

Low band : 10.7 ... 11.7 GHz

High band : 11.7 ... 12.75 GHz

NOISE FACTOR

Noise figure : 1 dB

OUTPUT FREQUENCY RANGE

Low band : 950 ... 1950 MHz

High band : 1100 ... 2150 MHz

POWER SUPPLY

Power consumption : max. 280 mA @13,5 V

PREPARED FOR

Number of clients : 6

Number of orbit positions : 1

SINGLE-CABLE OUTPUT

Output frequency : 950 ... 2150 MHz

Number of output channels : 4

Frequency of the output channels : 1210, 1420, 1680, 2040 MHz

TECHNICAL DATA

Outputs : 3 ; 1x SCR (gilded), 2x Legacy

Amplification : 57 dB

Feed reception : ø 40 mm

Connector type : F-Buchse

Impedance : 75 Ω

SCOPE OF DELIVERY

TechniSat SCR-LNB