



SCR-LNB

SCR-LNB with 2 legacy outputs

EAN	Colour	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
4019588178861	beige	0017/8886	344 g	292 g	14,5 x 6 x 11,5 cm	12,3 x 6,5 x 15 cm

TOP FEATURES

4 Receiver mit SCR-Unterstützung
anschließbar

2 Receiver über Legacy-Ausgang
anschließbar

SCR-Protokoll gemäß EN 50494
Wetterschutzgehäuse

Feed-ø 40 mm

LOCAL OSCILLATOR

Low band : 9,75 GHz

High band : 10,6 GHz

Accuracy : ± 1 MHz

Temperature drift : ± 3 MHz

Phase noise : -80 @10kHz

LNB CONTROL

Vertical : 11,5 ... 14 V

Horizontal : 16 ... 19 V

Band switch : 22 kHz

DiSEqC : 1

AMBIENT OPERATING CONDITIONS

Ambient temperature : -30 ... 60 °C

GENERAL CHARACTERISTICS

Colour *: white

INPUT FREQUENCY RANGE

Low band : 10,7 ... 11,7 GHz

High band : 11,7 ... 12,75 GHz

NOISE FACTOR

Noise figure : 1 dB

OUTPUT FREQUENCY RANGE

Low band : 950 ... 1.950 MHz

High band : 1.100 ... 2.150 MHz

POWER SUPPLY

Power consumption : max. 280 mA @13,5 V

SINGLE-CABLE OUTPUT

Output frequency : 950 ... 2.150 MHz

Number of output channels : 4

Frequency of the output channels : 1210,
1420, 1680, 2040 MHz

TECHNICAL DATA

Outputs : 3 ; 1x SCR (gilded), 2x Legacy

Connector type : F-Buchse

Amplification : 57 dB

Impedance : 75 Ω

Feed reception : ø 40 mm

SCOPE OF DELIVERY

TechniSat SCR-LNB

* black/white