



SlimFeed Universal-Quattro-LNB/40 mm for VARIO multifeed system

Digital-LNB for various participants, can be used with the TechniSat-Vario System and a Switch is needed.

EAN	Item no.	Colour	Weight (Box)	Weight	Device (W x H x D)	Box
4019588988804	0009/8880	white	240 g	200 g	4.50 x 8.50 x 14.00 cm	5.20 x 8.00 x 15.00 cm

LOCAL OSCILLATOR	Noise figure: 0.1 dB typ.	Impedance: 75 Ω
Low band: 9.75 GHz	OUTPUT FREQUENCY RANGE	Feed reception: ø 40 mm
High band: 10.6 GHz	Low band: 950 ... 1950 MHz	SCOPE OF DELIVERY
Accuracy: ± 0.5 MHz	High band: 1100 ... 2150 MHz	SlimFeed Universal-Quattro-LNB
Temperature drift: ± 1 MHz	POWER SUPPLY	
Phase noise: -85 dBc/Hz @10kHz	LNB voltage supply: 11 ... 20 V	
AMBIENT OPERATING CONDITIONS	Power consumption: 170 mA (Typ.)	
Ambient temperature: -40 ... 65 °C	PREPARED FOR	
Humidity: 5 ... 100 %	Number of orbit positions: 1	
INPUT FREQUENCY RANGE	TECHNICAL DATA	
Low band: 10.7 ... 11,7 GHz	Outputs: 4	
High band: 11.7 ... 12,75 GHz	Connector type: F-Buchse	
NOISE FACTOR	Amplification: 60 ... 64 dB	

KEYFEATURES

HDTV	Multiple subscribers
	1 orbit position