



SlimFeed Universal-Quattro-LNB/40 mm for VARIO multifeed system

Digital-LNB for various participants, can be used with the TechniSat-Vario System and a Switch is needed.

EAN	Colour	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
4019588988804	white	0009/8880	240 g	200 g	4.50 x 8.50 x 14.00 cm	5.20 x 8.00 x 15.00 cm

TOP FEATURES

Ultra low noise

Feed- \varnothing 40 mm

F-connectors

Weatherproof housing

LOCAL OSCILLATOR

Low band : 9.75 GHz

High band : 10.6 GHz

Accuracy : \pm 0.5 MHz

Temperature drift : \pm 1 MHz

Phase noise : -85 dBc/Hz @10kHz

AMBIENT OPERATING CONDITIONS

Ambient temperature : -40 ... 65 °C

Humidity : 5 ... 100 %

INPUT FREQUENCY RANGE

Low band : 10.7 ... 11,7 GHz

High band : 11.7 ... 12,75 GHz

NOISE FACTOR

Noise figure : 0.1 dB typ.

OUTPUT FREQUENCY RANGE

Low band : 950 ... 1950 MHz

High band : 1100 ... 2150 MHz

POWER SUPPLY

LNB voltage supply : 11 ... 20 V

Power consumption : 170 mA (Typ.)

PREPARED FOR

Number of orbit positions : 1

TECHNICAL DATA

Outputs : 4

Connector type : F-Buchse

Amplification : 60 ... 64 dB

Impedance : 75 Ω

Feed reception : \varnothing 40 mm

SCOPE OF DELIVERY

SlimFeed Universal-Quattro-LNB