



SATMAN 850 PLUS with SCR-LNB

EAN	Item no.	Colour	Weight (Box)	Weight
4019588085862	6085/8886	beige	8.8 kg	5.2 kg
4019588285866	6285/8886	fir green	8.8 kg	5.2 kg
4019588385863	6385/8886	slate grey	8.8 kg	5.2 kg
4019588485860	6485/8886	brick red	8.8 kg	5.2 kg
4019588785861	6785/8886	polar white	8.8 kg	5.2 kg
4019588585867	6585/8886	yellow with Smiley	8.8 kg	5.2 kg

TOP FEATURES

85 cm Spiegel aus erstklassigem Aluminium (beidseitig pulverbeschichtet)
 Inkl. SCR-LNB
 Ausgelegt für den 6-Teilnehmer-Empfang

4 Teilnehmer über SCR
 2 Teilnehmer über Legacy
 1 Orbitposition (z. B. Astra 19,2° Ost)

Optimal für Wand- und Dachmontage

LOCAL OSCILLATOR

Low band : 9.75 GHz

High band : 10.7 GHz

LNB CONTROL

Vertical : 11,5 - 14,5 V

Horizontal : 16 - 19 V

INPUT FREQUENCY RANGE

Low band : 10.7 ... 11.7 GHz

High band : 11.7 ... 12.75 GHz

NOISE FACTOR

Lower frequency range : 0.6 dB max.

Upper frequency range : 0.6 dB max.

OUTPUT FREQUENCY RANGE

Low band : 950 - 1950 MHz

High band : 1100 - 2150 MHz

PREPARED FOR

Number of orbit positions : 1

Number of clients : 6

TECHNICAL DATA

Rated measurement : 0.85 m

F/D : 0.67

G/T : 17.2 dB/K

Offset angle : 21 °

Gain : 38.2 dBi @11,3GHz

Mast Ø : 65 mm max.

Feed reception : LNB retaining clamp (40mm)