



DIGIT S3 HD

HDTV satellite receiver

EAN	Item no.	Colour	Weight (Box)	Weight	Device (W x H x D)	Box
4019588047129	0000/4712	black	1.03 kg	380 g	18.00 x 4.40 x 13.00 cm	26.00 x 8.00 x 17.00 cm

TOP FEATURES

Reception of free TV and radio channels via satellite (DVB-S/S2)

Electronic program guide (EPG)

ISIPRO: automatic updates of the programme list

Easy start-up via AutoInstall

HDTV: Hochauflösendes Fernsehen mit ausgezeichneter Bildqualität

HDTV: High-definition television with excellent image quality

AMBIENT OPERATING CONDITIONS

Humidity : 10 ... 75 %

Ambient temperature : 5 ... 35 °C

LNB CONTROL

Vertical : 14 V

Horizontal : 18 V

Band switch : 22 kHz

Current consumption : max. 400 mA (kurzschlussfest)

DiSEqC : 1.0 / 1.2

TECHNISAT ADDED VALUE SERVICES

ISIPRO : Yes

ISI-Mode : Yes

AUTOINSTALL : Yes

TECHNIFAMILY : Yes

SFI : Yes

INTERNET/NETWORK

Internet speed test : Yes

CONNECTIONS

HDMI™ (out) : 1

USB : 1 (USB 2.0)

Digital electric audio output : Yes

audio/video output analog (3.5 mm jack) : Yes TechniSat specific adapter set necessary (available at 0000/3649)

Ethernet 10/100 (RJ-45) : Yes

F socket : 1

DISPLAY

SD : Yes

HD : Yes

1080p : Yes

1080i : Yes

720p : Yes

576p : Yes

576i : Yes

HANDLING/COMFORT

Page memory : 1000

Teletext subtitles : Yes

Media Player : Yes

Remote control : Yes

Autostandby : Yes

Sleep timer : Yes

Channel presets : 4999

Selection regional channels : Yes

Teletext : Yes

Parental Control : Ja

Quick start : Yes

NETWORK & COMMUNICATION

100Base-T : Yes

IPv4 : Yes

TCP/IP : Yes

OTHER FEATURES

OSD languages : English, German, French, Greek, Italian, Dutch, Polish, Portuguese, Russian, Swedish, Spanish, Czech, Turkish, Hungarian

Total programme memory : 4999

POWER SUPPLY

Frequency : 50 Hz

Nominal voltage : 230 V

Mains adapter : external DC 12V/2A


SUPPORTED FORMATS & CODECS

Video-CODECS : MPEG-2, MPEG-4, H.264

Video-Formats : MTS, MPG, TS, TS4, M2TS, AVI, ASF

Picture-Formats : BMP, JPEG, GIF, PNG, TIFF

Audio-Formats : WAV, MP3, M4A, MP2, DDAC3

TUNER	TUNER - SAT	SCOPE OF DELIVERY
Tuner type : DigitalSat	Reception range : 950 ... 2150 MHz	DIGIT S3 HD, HDMI cable, remote control (incl. batteries), power supply, manual
DVB-S tuner : 1	Viterbi rates : 1/2, 2/3, 3/4, 5/6, 7/8 , (autom. Anpassung)	
Single Cable Solution (SatCR) : SCR1 = EN50494, SCR2 = EN50607	DVB-S : QPSK	
Satellite radio : Yes	DVB-S : 2 ... 45	
 <p>The terms HDMI, High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.</p>	DVB-S2 : 10 ... 31	
TECHNIROUTER ready : Yes	FEC : RS, LDPC, BCH	