



DIGIDISH 45 + 1 x DIGIT S3 HD

EAN	Colour	Item no.
4019588847125	beige	8614/4712
4019588947122	slate/grey	9614/4712
4019588647121	brick/red	6614/4712
4019588747128	polar/white	7614/4712
4019588547124	yellow with Smiley	5614/4712

TECHNISAT ADDED VALUE SERVICES

AUTOINSTALL : Yes

HANDLING/COMFORT

Ideal for camping : Yes

DIGIT S3 HD

ARTICLE INFORMATION	ISIPRO : Yes	720p : Yes
EAN : 4019588047129	ISI-Mode : Yes	576p : Yes
Item no. : 0000/4712	SFI : Yes	576i : Yes
Colour : black	AUTOINSTALL : Yes	
Weight (Box) : 1,03 kg	INTERNET/NETWORK	
Weight : 380 g	Internet speed test : Yes	
Device (W x H x D) : 18 x 4,4 x 13 cm	CONNECTIONS	
Box : 26 x 8 x 17 cm	HDMI™ (out) : 1	
AMBIENT OPERATING CONDITIONS	USB : 1 (USB 2.0)	
Ambient temperature : 5 ... 35 °C	Digital electric audio output (S/PDIF) : Yes	
Humidity : 10 ... 75 %	audio/video output analog (3.5 mm jack) : Yes TechniSat specific adapter set necessary (available at 0000/3649)	
LNB CONTROL	Ethernet 10/100 (RJ-45) : Yes	
Vertical : 14 V	F socket : 1	
Horizontal : 18 V	DISPLAY	
Band switch : 22 kHz	SD : Yes	
Current consumption : max. 400 mA (kurzschlussfest)	HD : Yes	
DiSEqC : 1.0 / 1.2	1080p : Yes	
TECHNISAT ADDED VALUE SERVICES	1080i : Yes	
TECHNIFAMILY : Yes		

HANDLING/COMFORT	OSD languages : English, German, French, Greek, Italian, Dutch, Polish, Portuguese, Russian, Swedish, Spanish, Czech, Turkish, Hungarian	DVB-S tuner : 1
Page memory : 1.000	Total programme memory : 4.999	Single Cable Solution (SatCR) : SCR1 = EN50494, SCR2 = EN50607
Teletext subtitles : Yes	POWER CONSUMPTION	Satellite radio : Yes
Media Player : Yes	Standby LED : 0,3 W	Internet radio : Yes
Parental Control : Ja	In operation : 6,3 W	Reception on : HD-TV, SD-TV
Teletext : Yes	POWER SUPPLY	TECHNIROUTER ready : Yes
Channel presets : 4.999	Nominal voltage : 230 V	TUNER - SAT
Sleep timer : Yes	Frequency : 50 Hz	Reception range : 950 ... 2.150 MHz
Quick start : Yes	Mains adapter : external DC 12V/2A	Viterbi rates : 1/2, 2/3, 3/4, 5/6, 7/8 , (autom. Anpassung)
Autostandby : Yes	SUPPORTED FORMATS & CODECS	DVB-S : QPSK
Remote control : Yes	Video-Codecs : MPEG-2, MPEG-4, H.264	DVB-S : 2 ... 45
Selection regional channels : Yes	Video-Formats : MTS, MPG, TS, TS4, M2TS, AVI, ASF	DVB-S2 : 8PSK - QPSK
NETWORK & COMMUNICATION	Picture-Formats : BMP, JPEG, GIF, PNG, TIFF	DVB-S2 : 10 ... 31
100Base-T : Yes	Audio-Formats : WAV, MP3, M4A, MP2, DDAC3	FEC : RS, LDPC, BCH
IPv4 : Yes	TUNER	
TCP/IP : Yes	Tuner type : DigitalSat	
OTHER FEATURES		

DIGIDISH 45, Universal-Twin-LNB

ARTICLE INFORMATION	Band switch : 22 kHz	Low band : 950 - 1.950 MHz
EAN : 4019588452824	GENERAL CHARACTERISTICS	High band : 1.100 - 2.150 MHz
Item no. : 1045/2882	Material : Aluminium	POWER SUPPLY
Colour : beige	Material strength : 1 mm	LNB voltage supply : 11,5 ... 19 V
Weight (Box) : 3,7 kg	Coating : Powder-coated on both sites	Power consumption : max. 190 mA
Weight : 2,9 kg	Colour *: beige, polar white, slate-grey, brick-red	TECHNICAL DATA
Device (W x H x D) : 45 x 48 cm	including Wall bracket : Yes	Rated measurement : 0,45 m
Box : 51 x 51 x 23 cm	INPUT FREQUENCY RANGE	F/D : 0,6
LOCAL OSCILLATOR	Low band : 10,7 ... 11,7 GHz	Offset angle : 30 °
Low band : 9,75 GHz	High band : 11,7 ... 12,75 GHz	Gain : 32,2 dBi @11,3 GHz
High band : 10,7 GHz	NOISE FACTOR	Feed reception : 40 mm
LNB CONTROL	Lower frequency range : 0,7 dB max.	
Vertical : 11,5 - 14 V	Upper frequency range : 0,7 dB max.	
Horizontal : 16 - 19 V	OUTPUT FREQUENCY RANGE	

black/white
black/white
* black/white