



## DIGIDISH 45 + 1 x DIGIT S3 HD

EAN	Colour	Item no.
4019588847125	beige	8614/4712
4019588947122	slate/grey	9614/4712
4019588647121	brick/red	6614/4712
4019588747128	polar/white	7614/4712
4019588547124	yellow with Smiley	5614/4712

### TECHNISAT ADDED VALUE SERVICES

AUTOINSTALL : Yes

### HANDLING/COMFORT

Ideal for camping : Yes

### DIGIDISH 45, Universal-Twin-LNB

<b>ARTICLE INFORMATION</b>	Horizontal : 16 - 19 V	Power consumption : max. 190 mA
EAN : 4019588452824	Band switch : 22 kHz	<b>PREPARED FOR</b>
Item no. : 1045/2882	<b>INPUT FREQUENCY RANGE</b>	Number of orbit positions : 1
Colour : beige	Low band : 10.7 ... 11.7 GHz	Number of clients : 2
Weight (Box) : 3.7 kg	High band : 11.7 ... 12.75 GHz	<b>TECHNICAL DATA</b>
Weight : 2.9 kg	<b>NOISE FACTOR</b>	Rated measurement : 0.45 m
Device (W x H x D) : 45.00 x 48.00 cm	Lower frequency range : 0.7 dB max.	F/D : 0.6
Box : 51.00 x 51.00 x 23.00 cm	Upper frequency range : 0.7 dB max.	Offset angle : 30 °
<b>LOCAL OSCILLATOR</b>	<b>OUTPUT FREQUENCY RANGE</b>	Gain : 32.2 dBi @11,3 GHz
Low band : 9.75 GHz	Low band : 950 - 1950 MHz	Feed reception : 40 mm
High band : 10.7 GHz	High band : 1100 - 2150 MHz	
<b>LNB CONTROL</b>	<b>POWER SUPPLY</b>	
Vertical : 11,5 - 14 V	LNB voltage supply : 11.5 ... 19 V	

### DIGIT S3 HD

<b>ARTICLE INFORMATION</b>
EAN : 4019588047129
Item no. : 0000/4712
Colour : black
Weight (Box) : 1.03 kg
Weight : 380 g
Device (W x H x D) : 18.00 x 4.40 x 13.00 cm
Box : 26.00 x 8.00 x 17.00 cm
<b>AMBIENT OPERATING CONDITIONS</b>
Humidity : 10 ... 75 %
Ambient temperature : 5 ... 35 °C
<b>LNB CONTROL</b>
Vertical : 14 V
Horizontal : 18 V
Band switch : 22 kHz
Current consumption : max. 400 mA (kurzschlussfest)
DiSEqC : 1.0 / 1.2
<b>TECHNISAT ADDED VALUE SERVICES</b>
ISIPRO : Yes
TECHNIFAMILY : Yes
AUTOINSTALL : Yes
SFI : Yes
ISI-Mode : Yes
<b>INTERNET/NETWORK</b>
Internet speed test : Yes
<b>CONNECTIONS</b>
HDMI (out) : 1
USB : 1 (USB 2.0)
Digital electric audio output : Yes

audio/video output analog (3.5 mm jack) : Yes TechniSat specific adapter set necessary (available at 0000/3649)
Ethernet 10/100 (RJ-45) : Yes
F socket : Yes
<b>DISPLAY</b>
SD : Yes
HD : Yes
1080p : Yes
1080i : Yes
720p : Yes
576p : Yes
576i : Yes
<b>HANDLING/COMFORT</b>
Page memory : 1000
Teletext subtitles : Yes
Media Player : Yes
Remote control : Yes
Autostandby : Yes
Selection regional channels : Yes
Channel presets : 4999
Sleep timer : Yes
Quick start : Yes
Teletext : Yes
Parental Control : Ja
<b>NETWORK &amp; COMMUNICATION</b>
IPv4 : Yes
100Base-T : Yes
TCP/IP : Yes
<b>OTHER FEATURES</b>

OSD languages : English, German, French, Greek, Italian, Dutch, Polish, Portuguese, Russian, Swedish, Spanish, Czech, Turkish, Hungarian
Total programme memory : 4999
<b>POWER SUPPLY</b>
Frequency : 50 Hz
Nominal voltage : 230 V
Mains adapter : external DC 12V/2A
<b>SUPPORTED FORMATS &amp; CODECS</b>
Video-CODECS : MPEG-2, MPEG-4, H.264
Video-Formats : MTS, MPG, TS, TS4, M2TS, AVI, ASF
Picture-Formats : BMP, JPEG, GIF, PNG, TIFF
Audio-Formats : WAV, MP3, M4A, MP2, DDAC3
<b>TUNER</b>
Tuner type : DigitalSat
DVB-S tuner : 1
Single Cable Solution (SatCR) : SCR1 = EN50494, SCR2 = EN50607
Satellite radio : Yes
Internet radio : Yes
Reception on : HD-TV, SD-TV
TECHNIROUTER ready : Yes
<b>TUNER - SAT</b>
Reception range : 950 ... 2150 MHz
Viterbi rates : 1/2, 2/3, 3/4, 5/6, 7/8 , (autom. Anpassung)
DVB-S : QPSK
DVB-S : 2 ... 45 Mbaud
DVB-S2 : 8PSK - QPSK
DVB-S2 : 10 ... 31 Mbaud
FEC : RS, LDPC, BCH

**Testurteil(e) DIGIDISH 45 + 1 x DIGIT S3 HD**



Zweiter Platz in der Kategorie Sat-Anlagen bei der Leserwahl zum König-Kunde-Award 2014 (Camping, Cars & Caravans)

black/white  
black/white