



## TV-SAT AMPLIFIER BBV 2400-R

For amplification of terrestrial and satellite signals

EAN	Colour	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
4019588231283	white	0002/3128	352 g	328 g	13.00 x 4.00 x 6.50 cm	14.00 x 5.00 x 9.70 cm

### AMBIENT OPERATING CONDITIONS

Ambient temperature: -20 ... 50 °C

### AMPLIFICATION

Return path: -4 dB

Terrestrial: 14 ... 18 dB (slop)

Sat: 18 ... 25 dB (slop)

### POWER SUPPLY

Mains adapter: internal

Nominal voltage: 230 V ~

Frequency: 50 ... 60 Hz

Effective output: 4 W

### RECEPTION RANGE

Return path: 5 ... 65 MHz

Terrestrial: 87 ... 862 MHz

Sat: 950 ... 2400 MHz

### TECHNICAL DATA

Shielding factor:  $\geq 75$  dB EN 50083-2 (Class A)

Impedance: 75  $\Omega$

Connector type: F female/F female

Return loss:  $\leq 10$  dB

### SCOPE OF DELIVERY

TV-SAT VERSTÄRKER BBV 2400-R, mounting instructions