



2 YEARS
WARRANTY

BESSER
MADE IN
GERMANY

Line Amplifier 5Z2/NT

Amplifier for signal gain for 1 orbital position

EAN	Colour	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
4019588132412	silver/yellow	0001/3241	400 g	200 g	15.00 x 5.50 x 3.00 cm	22.20 x 11.00 x 10.40 cm

TOP FEATURES

Kompensiert die Dämpfung von bis zu 40 m Koaxkabel

AMBIENT OPERATING CONDITIONS

Ambient temperature: -25 ... 55 °C

AMPLIFICATION

Sat: 7 ... 12 dB fest, schräglagenentzerrt

Terrestrial: 5 ... 10 dB einstellbar

DECOUPLING

Trunks: 50 dB

POWER CONSUMPTION

In operation: 2.2 W

POWER SUPPLY

Nominal voltage: 15 V DC

Mains adapter: external (Optional)

Power consumption: typ. 120 mA @15 V

RECEPTION RANGE

Sat: 950 ... 2150 MHz

Terrestrial: 87 ... 862 MHz

TECHNICAL DATA

Satellite inputs: 4

Terrestrial input: 1

SCOPE OF DELIVERY

Line Amplifier 5Z2, power supply, instruction manual