



2 YEARS
WARRANTY

**BESSER
MADE IN
GERMANY**

Active 2-way tap 5/2A

Active 2-way tap for 1 orbital position

EAN	Item no.	Colour	Weight (Box)	Weight	Box	Device (W x H x D)
4019588032439	0000/3243	silver	400 g	300 g	21.30 x 9.60 x 5.70 cm	18.30 x 6.90 x 2.60 cm

TOP FEATURES

Gleiches Rastermaß der F-Buchsen wie TECHNISWITCH und TECHNISYSTEM

AMBIENT OPERATING CONDITIONS

Ambient temperature: -25 ... 55 °C

AMPLIFICATION

Sat: 3 ... 6 dB fest

Terrestrial: 5 dB einstellbar

DECOUPLING

Output: 45 dB

Trunks: 60 dB

POWER SUPPLY

Power consumption: typ. 130 mA @15V

RECEPTION RANGE

Sat: 950 ... 2150 MHz

Terrestrial: 87 ... 862 MHz

TECHNICAL DATA

Satellite inputs: 4

Terrestrial input: 1

TRANSMISSION LOSS

Sat: 0.6 ... 1 dB

Terrestrial: 1.2 dB

SCOPE OF DELIVERY

Active 2-way tap 5/2A, instruction manual