



EUTELASTRASAT 850, 2 participant

With the TechniSat EUTELASTRASAT appliance you receive the TV and radio programmes of ASTRA 19.2° East and EUTELSAT 13° East

EAN	Item no.	Colour	Weight (Box)	Weight	Box
4019588297081	9702/8882	beige	9.6 kg	6 kg	88.00 x 95.00 x 24.00 cm
4019588732827	9732/8882	slate/grey	9.6 kg	6 kg	88.00 x 95.00 x 24.00 cm
4019588742826	9742/8882	brick/red	9.6 kg	6 kg	88.00 x 95.00 x 24.00 cm
4019588722828	9722/8882	fir/green			88.00 x 95.00 x 24.00 cm

LOCAL OSCILLATOR

Low band: 9.75 GHz \pm 3MHz

High band: 10.6 GHz \pm 3MHz

LNB CONTROL

Vertical: 11,5 - 14,5 V

Horizontal: 16 - 19 V

GENERAL CHARACTERISTICS

Material: Aluminium

Top features: Für 2 Teilnehmer

Top features: 2 Orbitpositionen (Astra 19,2° Ost und Eutelsat Hotbird 13° Ost)

Top features: Optimal für Dachmontage

Material strength: 1.6 mm

Coating: Powder-coated on both sites

INPUT FREQUENCY RANGE

TECHNISWITCH 2/1 (DiSEqC position relais)

ARTICLE INFORMATION

Low band: 10.7 - 11.7 GHz

High band: 11.7 - 12.75 GHz

NOISE FACTOR

Lower frequency range: 0.6 dB max.

Upper frequency range: 0.6 dB max.

OUTPUT FREQUENCY RANGE

Low band: 950 - 1950 MHz

High band: 1100 - 2150 MHz

TECHNICAL DATA

Rated measurement: 0.85 m

F/D: 0.67

G/T: 17.2 dB/K

Gain: 38.2 dBi @11,3 GHz

Offset angle: 21 °

Satellite positions: Eutelsat 13° east, ASTRA 19,2° east

Mast \varnothing : 65 mm max.

Feed reception: for UNYSAT-Universal-LNB

SCOPE OF DELIVERY

Satellite dish, 2x Unysat V/H LNB in a weatherproof housing, AZ/EL mount (with Multifeed-mount), 1x TechniSwitch 2/1 DiSEqC switch, screws, tools, instruction manual

Multifeed extension ASTRA/EUTELSAT

ARTICLE INFORMATION

UNYSAT Universal-Twin-LNB

ARTICLE INFORMATION

KEYFEATURES

HDTV

2 subscribers

2 orbit positions

Testurteil(e) EUTELASTRASAT 850, 2 participant



Leserwahl König Kunde
Award - 2. Platz in der
Kategorie Sat-Anlagen
(Camping, Cars & Caravans)