



5 YEARS
WARRANTY

BESSER
MADE IN
GERMANY

TECHNIROUTER 5/1x8 G

Digital single-cablesolution for the distribution of satellite signals from one orbital position via a cable harness for an existing cable structure

EAN	Colour	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
4019588032903	blue/yellow	0000/3290	500 g	240 g	14.00 x 11.50 x 3.20 cm	24.50 x 13.50 x 5.50 cm

TOP FEATURES

Infeed of digital satellite signals into existing cable structures

For tree structures, series connections and star distributions

Suitable for new satellite installations and enhancements

Feedback channel for simultaneous usage of the Internet and telephone facility in the in-house satellite distribution unit

Basic units for up to 8 subscribers, can be enhanced through cascades

1 satellite position can be received without restrictions

LNB CONTROL

Vertical : 13 V über VL

AMBIENT OPERATING CONDITIONS

Ambient temperature : -25 ... 55 °C

Humidity : 10 ... 75 %

AMPLIFICATION

Sat : 13 ... 18 dB

Terrestrial : -1 dB

DECOUPLING

Trunks : 45 dB

POWER SUPPLY

Nominal voltage : 230 V

Frequency : 50 Hz

Mains adapter : external DC 12V/0,46A (nur für LNB)

RECEPTION RANGE

Terrestrial : 47 ... 862 MHz

Sat : 950 ... 2150 MHz

SINGLE-CABLE OUTPUT

Output frequency : 47 ... 2150 MHz

Number of output channels : 8

Frequency of the output channels : 1284, 1400, 1516, 1632, 1748, 1864, 1980, 2096 MHz

Frequency SAT : 950 ... 2150 MHz

Frequency DVB-T : 47 ... 862 MHz

TECHNICAL DATA

Satellite inputs : 4

Terrestrial input : 1

Number of cable connections : 1

Subscribers per cable : maximal 8

TUNER

TECHNIROUTER ready : Yes

SCOPE OF DELIVERY

TechniRouter 5/1x8 G, Instruction manual, power supply