



DIGICORDER HD S2

First-class HDTV receiver with integrated hard disc, which makes it possible to watch TV in a quality previously unheard of

EAN	Item no.	Colour	Weight (Box)	Weight	Device (W x H x D)	Box
4019588047204	0000/4720	black	2,9 kg	2,66 kg	37 x 6,5 x 22 cm	44,5 x 12 x 28 cm

LNB CONTROL	Standby LED : < 1 W
DiSEqC : 1	In operation : < 24 W
Horizontal : 18 V	POWER SUPPLY
Vertical : 14 V	Mains adapter : internal
Band switch : 22 kHz	Nominal voltage : 180 ... 250 V
TECHNISAT ADDED VALUE SERVICES	Frequency : 50 Hz
AUTOINSTALL : Yes	TUNER
AUDIO	Tuner type : Twin-Tuner
AC3 Dolby Digital bitstream out : Yes	Single Cable Solution (SatCR) : SCR1 = EN50494
CONNECTIONS	Input impedance : 75 Ω
HDMI™ (out) : 1	TECHNIROUTER ready : Yes
Common Interface (CI) : 2	Reception on : HDTV (Mpeg-4+2) SD (MPEG-2)
Digital electric audio output (S/PDIF) : Yes	TUNER - SAT
Digital optical audio out : Yes	DVB-S : QPSK
Audio out analogue (RCA) : Yes	Viterbi rates : 1/2, 2/3, 3/4, 5/6, 7/8 , (autom. Anpassung)
YUV (component output) : 1	DVB-S2 : 8PSK - QPSK
Scart : 2	DVB-S : 2 ... 45
Video Cinch out : 1	FEC : Viterbi and Reed-Solomon
Ethernet 10/100 (RJ-45) : Yes (RJ-45)	DVB-S2 : 10 ... 31 (8PSK), 10...30Mbaud/s (QPSK)
F socket : 2	Reception range : 2 x 950 ... 2.150 MHz
RS-232 : 1	SCOPE OF DELIVERY
DECRYPTION SYSTEM	Scope of delivery DigiCorder HD S2 1 mains cable 1 SCART cable 1 remote control 2 batteries (1.5 V AAA) Operating manual Guarantee card
Conax : Yes	
CI : Yes	
DISPLAY	
Picture in Picture (PIP) : Yes (2 x SD, 1 x SD u. 1 x HD)	
Freeze frame : Yes	
Zoom : Yes	
SD : Yes	
720p : Yes	
1080i : Yes	
HD : Yes	
OTHER FEATURES	
Total programme memory : 5.000	
Loophrough : Yes	
POWER CONSUMPTION	



The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.