



2 YEARS
WARRANTY

BESSER
MADE IN
GERMANY

TECHNIROUTER 9/1x8 G

Digital single-cable solution with PIN code technology for the distribution of signals from two satellite positions with a cable harness using an existing cable structure

EAN	Colour	Item no.	Weight (Box)	Weight	Box
4019588032941	blue/yellow	0000/3294	800 g	500 g	31.80 x 20.00 x 4.50 cm

TOP FEATURES

Einspeisung von digitalen Sat-Signalen in vorhandene Kabelstrukturen

2 Orbitpositionen ohne Einschränkung mit 2 Quatro-LNB zu empfangen

Keine weitere Kabelverlegung erforderlich

Eingang zum Empfang von Terrestrischen Signalen

AMBIENT OPERATING CONDITIONS

Humidity : 10 ... 75 %

Ambient temperature : -25 ... 55 °C

AMPLIFICATION

Sat : 13 ... 18 dB

Terrestrial : -1 dB

DECOUPLING

Trunks : 45 dB

POWER SUPPLY

Frequency : 50 Hz

Nominal voltage : 230 V

Mains adapter : internal

RECEPTION RANGE

Sat : 950 ... 2150 MHz

Terrestrial : 47 ... 862 MHz

SINGLE-CABLE OUTPUT

Output frequency : 47 ... 2150 MHz

Number of output channels : 8

Frequency of the output channels : 1284, 1400, 1516, 1632, 1748, 1864, 1980, 2096 MHz

Frequency SAT : 950 ... 2150 MHz

Frequency DVB-T : 47 ... 862 MHz

TECHNICAL DATA

Satellite inputs : 8

Terrestrial input : 1

Number of cable connections : 1

Subscribers per cable : maximal 8