



UNYSAT Quatro-Switch-LNB

Digital-LNB for four participants

EAN	Colour	Item no.	Weight (Box)	Weight	Box	Device (W x H x D)
4019588089808	grey	0000/8980	500 g	440 g	10.00 x 22.50 x 19.00 cm	7.50 x 13.00 x 17.50 cm

LNB CONTROL	Low band: 10,7 ... 11,7 GHz	Amplification: 52 ... 65 dB
Vertical: 16 ... 19 V	High band: 11,7 ... 12,75 GHz	Impedance: 75 Ω
Horizontal: 11,5 ... 14,5 V	NOISE FACTOR	Connector type: F-Buchse
Band switch: 22 kHz	Noise figure: 0.6 dB	Feed reception: Für SATMAN
Low band: 9,75 GHz	OUTPUT FREQUENCY RANGE	
High band: 10,6 GHz	Low band: 950 ... 1950 MHz	
Accuracy: ± 1 MHz	High band: 1100 ... 2150 MHz	
Temperature drift: ± 3 MHz	POWER SUPPLY	
Phase noise: -75 dBc/Hz @10kHz	LNB voltage supply: 11.5 ... 19 V	
Humidity: 10 ... 90 %	Power consumption: max. 190 mA	
Ambient temperature: -30 ... 60 °C	TECHNICAL DATA	
INPUT FREQUENCY RANGE	Outputs: 4	

KEYFEATURES

HDTV	4 subscribers
	1 orbit position

Testurteil(e) UNYSAT Quatro-Switch-LNB



Note: sehr gut | 92,1%
SATVISION (04/2011)