



HDTV 32

32 inch multimedia television set (Full-HD) with a discreetly designed front frame, integrated Dual HDTV multi-tuner and an integrated hard drive

EAN	Item no.	Colour	Weight (Box)	Weight	Unit without stand (W x H x D)	Device (W x H x D)	Box
4019588332300	5332/0306	black/silver metallic	25 kg	21 kg	805 x 620 x 115 mm	80,5 x 65,5 x 20 cm	101 x 80 x 31 cm
4019588332317	5332/0316	black/titanium metallic	25 kg	21 kg	805 x 620 x 115 mm	80,5 x 65,5 x 20 cm	101 x 80 x 31 cm
4019588332324	5332/0326	black/black	25 kg	21 kg	805 x 620 x 115 mm	80,5 x 65,5 x 20 cm	101 x 80 x 31 cm
4019588332119	5332/0611	black/high	24,5 kg	24,5 kg	805 x 620 x 115 mm	80,5 x 65,5 x 20 cm	101 x 80 x 31 cm
4019588332614	5332/0601	black/andalusi an	24,5 kg	24,5 kg	805 x 620 x 115 mm	80,5 x 65,5 x 20 cm	101 x 80 x 31 cm
4019588332621	5332/0602	black/tuscany	24,5 kg	24,5 kg	805 x 620 x 115 mm	80,5 x 65,5 x 20 cm	101 x 80 x 31 cm

TOP FEATURES

Dual-HDTV-Multituner zum Empfang von DigitalSat, Kabel und DVB-T ohne zusätzlichen Receiver

2-Wege-Lautsprecher im Bassreflexgehäuse

Integrierte 250-GB-Festplatte/Timeshift
2xCI-Schnittstelle und Conax Smartcard-Leser

Netzwerk- und USB-Schnittstelle
Standbild/Zoom/PiP/PaP/PaT

AMBIENT OPERATING CONDITIONS

Ambient temperature : 5 - 35 °C

Humidity : 10 - 75 %

LNB CONTROL

Band switch : 22 kHz

Horizontal : <20 V without load, > 17.2 V at 400 mA / LNB shut-off standby mode V

DiSEqC : DiSEqC 1.0 / DiSEqC 1.x Sat Channel Router

Current consumption : 400 mA

Vertical : <14 V without load, > 11.5 V at 400 mA V

TECHNISAT ADDED VALUE SERVICES

AUTOINSTALL : Yes

AUDIO	DISPLAY	OTHER FEATURES
Speakers : 2 x 2-way sound system with bass reflex	Size (cm) : 81 cm	OSD languages : Italian, Swedish, Czech, Dutch, Turkish, Spanish, Greek, Portuguese, German, Russian, Polish, English, French, Hungarian
AC3 Dolby Digital bitstream out : Yes	Format : 16:9	Total programme memory : 5.000
CONNECTIONS	Contrast ratio : 3.000:1	Regional channel selection : Yes
HDMI™ (in) : 3	Brightness : 500 cd/m²	POWER CONSUMPTION
Common Interface (CI) : 2	Picture in Picture (PIP) : Yes (2 x SD, 1 x SD u. 1 x HD)	SFIplus updating : 43 W
Smartcard reader : Yes	Response time : 8 ms	Software update : 43 W
Subwoofer output : Yes	Angle of view : 178° / 178°	Energy class : D
VGA : Yes	Picture and Picture (PAP) : Yes	Standby fast start : 34 W
YUV (component input) : Yes	Freeze frame : Yes	Standby LED : 0,09 W
Scart : 2	Zoom : Yes	In operation : 114 W
S Video : Yes	SD : Yes	annual energy consumption when switched on : 166 kilowatt hour per annum
Video IN : 1	Resolution (vertical and horizontal) : 1920 x 1080	Off status : 0
Ethernet 10/100 (RJ-45) : Yes (RJ-45)	Type : TFT-LCD "Full HD"	Power switch : Yes
F socket : 2	1080i : Yes	POWER SUPPLY
IEC-Connector : Yes	720p : Yes	Mains adapter : internal
RS-232 : 0	HD : Yes	Nominal voltage : 230 V
DECRYPTION SYSTEM	Size (inches) : 32	Frequency : 50 Hz
Conax : Yes	GENERAL CHARACTERISTICS	TUNER
CI : Yes	Hard drive : 250 GigaByte	Tuner type : Dual-HDTV-Multituner
DIMENSIONS / WEIGHT	HANDLING/COMFORT	DVB-S tuner : 2
Set depth without stand : 115 mm	Alarm : Yes	DVB-C Tuner : 2
Set height without stand : 620 mm	Sleep timer : Yes	DVB-T Tuner : 2
Set width without stand : 805 mm	Clock : Yes	Analogue UHF/VHF/CATV tuner : 2
	HOTEL MODE	Reception on : HDTV (Mpeg-4+2) SD (MPEG-2)
	Customisable start screen : Yes	TECHNIROUTER ready : Yes
	Configurable on times : Yes	Input impedance : 75 Ω
	Energy card function : Yes	TUNER - ANALOGUE
	USB cloning function : Yes	Video standards : PAL, SECAM
	Multimedia connectors : Yes	Reception range : 46 ... 860 MHz
	Menu locking : Yes	TUNER - CABLE
	Radio mode : Yes	Symbol rate : 1,7 ... 7
	Mixing of channel slots : Yes	FEC : Reed-Solomon
	Multicode remote control : Yes	Reception range : 47 ... 862 MHz
	Fireproofed housing : Yes	Demodulation : 16/32/64/128/256 QAM
	MATERIALS CONTAINED	TUNER - SAT
	Lead : Yes	Reception range : 950 ... 2.150 MHz
		DVB-S : QPSK
		Viterbi rates : 1/2, 2/3, 3/4, 5/6, 7/8
		DVB-S : 1 ... 45
		FEC : Viterbi and Reed-Solomon
		DVB-S2 : 8PSK - QPSK
		DVB-S2 : 10 ... 31
		TUNER - TERRESTRIAL
		Reception range 2 : 470 ... 860 MHz
		Reception range 1 : 174 ... 230 MHz

Bitrate : 4 ... 32

Voltage supply : 0,05 V

Demodulation : COFDM

Transmission mode : 2k/8k

Power supply : 5 A

WALL BRACKET

VESA wall mounting standards : VESA 400 x 200

SCOPE OF DELIVERY

HDTV 32 Plus, mains power cable, fully specified remote control, 2 batteries (1.5 V AAA), angled screwdriver, operating manual, quick-and-easy manual, guarantee documents



The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.