



Base unit BS4 Professional

Cable head end Base unit for eight SkyCable cards

EAN	Item no.	Colour	Weight (Box)	Weight	Box	Device (W x H x D)
4019588059603	0000/5960	white/blue	24.5 kg	22.1 kg	55.00 x 53.00 x 44.00 cm	43.50 x 40.00 x 35.00 cm
4019588159600	0001/5960	RAL 9002				

CONFIGURATION, MONITORING

Network interface: RJ45, Ethernet, 100BaseT, TCP/IP, SNMP

Service connection: RJ25, serial, for TechniNet Programmer

GENERAL

Power supply: 100 ... 250 VAC / 50 ... 60 Hz

Power input: Max. 250 W

Nominal temperature range: 0 ... 45 °C

Relative humidity: 0 ... 80 %

EMV: EN50083-2, EN55022:2006+A1:2007, EN55024:1998+A1:2001+A2:2003, EN61000-3-2:2006, EN61000-3-3:2008

Security: VDE 0855-1, DIN EN 60728-11:2005

POWER CONSUMPTION

Power switch: Yes

POWER SUPPLY

Frequency: 50 ... 60 Hz

Nominal voltage: 230 V

Mains adapter: internal

RF OUTPUT

Reception range: 42 ... 862 MHz

input / output: F-socket

Impedance: 75 Ω

Output level: ≤ 107 dBμV (± 3 dB) @ 256-QAM typisch

SAT IF INPUT / MULTISWITCH

Reception range: 950 ... 2150 MHz

input / output: F-socket

Impedance: 75 Ω

Input level: 50 ... 90 dBμV (Summenpegel)

LNB voltage supply: 13 / 18 V & 22kHz

LNB power supply: Max. 300 mA je Eingang

SCOPE OF DELIVERY

TechniNet BS4 Professional base unit, Multi Wall Mount + 19" rack, power cord, installation manual

KEYFEATURES

HDTV

Multiple subscribers

1 orbit position