



UNYSAT Universal-Quatro-LNB

Digital-LNB for various participants

EAN	Colour	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
4019588088801	grey	0000/8880	500 g	440 g	7 x 9,7 x 17,5 cm	10 x 22,5 x 19 cm

TOP FEATURES

For multi-switch distribution

Special weatherproof housing for the excellent receiving electronics

Suitable for all TechniSat SATMAN dishes

Quick and easy assembly without a retaining clamp

LOCAL OSCILLATOR

Low band : 9,75 GHz

High band : 10,6 GHz

Accuracy : ± 1 MHz

Temperature drift : ± 3 MHz

Phase noise : -75 @10kHz

AMBIENT OPERATING CONDITIONS

Humidity : 10 ... 90 %

Ambient temperature : -30 ... 60 °C

INPUT FREQUENCY RANGE

Low band : 10,7 ... 11,7 GHz

High band : 11,7 ... 12,75 GHz

NOISE FACTOR

Noise figure : 0,6 dB

OUTPUT FREQUENCY RANGE

Low band : 950 ... 1.950 MHz

High band : 1.100 ... 2.150 MHz

POWER SUPPLY

LNB voltage supply : 11,5 ... 19 V

Power consumption : max. 250 mA

TECHNICAL DATA

Outputs : 4

Impedance : 75 Ω

Connector type : F-Buchse

Feed reception : Für SATMAN

Amplification : 52 ... 65 dB