



**2 YEARS**  
WARRANTY

**ENERGY**  
SAVER

**BESSER**  
MADE IN  
GERMANY

## TECHNISYSTEM 5/8 G2

Multi-switch system with connection possibility of 4 ZF levels for distribution to up to 8 participants

EAN	Colour	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
4019588132498	blue/yellow	0001/3249	1 kg	300 g	17.20 x 11.50 x 3.20 cm	17.40 x 13.50 x 10.50 cm

### TOP FEATURES

Professionelles Multischaltersystem für Großanlagen

Mit Schräglagenentzerrung

Ohne Dämpfung im Sat-Bereich

Für Quattro-LNB

### AMBIENT OPERATING CONDITIONS

Ambient temperature : -25 ... 55 °C

### AMPLIFICATION

Sat : -2 ... 3 dB

Terrestrial : -4 ... -1 dB

### DECOUPLING

Output : > 35 dB

Trunks : 40 dB

### POWER SUPPLY

Mains adapter : extern DC 15V/1,2A

Nominal voltage : 100 ... 240 V

Frequency : 50 ... 60 Hz

### RECEPTION RANGE

Sat : 950 ... 2150 MHz

Terrestrial : 47 ... 862 MHz

### TECHNICAL DATA

Satellite inputs : 4

Terrestrial input : 1

Outputs : 8

Distribution length : 100 m

### SCOPE OF DELIVERY

TECHNISYSTEM 5/8 G2, Power supply,  
Manual

## Testurteil(e) TECHNISYSTEM 5/8 G2



Note: sehr gut (92,8%)  
SatVision (06/2011)