



## 4-way satellite splitter

for the 4-fold distribution of Sat signals

EAN	Item no.	Colour	Weight (Box)	Weight	Device (W x H x D)	Box
4019588031111	0000/3111	silver	100 g	100 g	8.50 x 5.30 x 2.20 cm	9.10 x 10.00 x 2.40 cm

<b>DECOUPLING</b>	950 - 1750 MHz: Typ. 10 dB	950 - 1750 MHz: Typ. 8 dB (± 1)
5 - 862 MHz: Typ. 20 dB	1750 - 2150 MHz: Typ. 10 dB	1750 - 2150 MHz: Typ. 9 dB (± 1)
950 - 1750 MHz: Typ. 20 dB	<b>TECHNICAL DATA</b>	
1750 - 2150 MHz: Typ. 16 dB	Input: 1	
<b>GENERAL CHARACTERISTICS</b>	Outputs: 4	
Top features: DC power pass	Frequency range: 5 ... 2150 MHz	
Top features: diode decoupled	Shielding factor: ≥ 75 dB EN 50083-2 (Class A)	
Top features: DiSEqC-compatible	Connector type: F female	
Top features: TECHNIROUTER-compatible	Impedance: 75 Ω	
<b>RETURN LOSS</b>	<b>TRANSMISSION LOSS</b>	
5 - 862 MHz: Typ. 12 dB	5 - 862 MHz: Typ. 8 dB (± 1)	