



## SKYTENNE

Digital satellite dish with a diameter of 85 cm ready for the reception of four Orbital positions at the same time without any rotor. Perfect for Multi-participant reception(with multi switch)!

EAN	Item no.	Colour	Weight (Box)	Weight	Box
4019588850446	6085/1544	beige	10.2 kg	6.6 kg	87.00 x 95.00 x 24.00 cm
4019588853447	6385/1544	slate/grey	10.2 kg	6.6 kg	87.00 x 95.00 x 24.00 cm
4019588854444	6485/1544	brick/red	10.2 kg	6.6 kg	87.00 x 95.00 x 24.00 cm
4019588852440	6285/1544	fir/green	10.2 kg	6.6 kg	87.00 x 95.00 x 24.00 cm
4019588857445	6785/1544	polar/white	10.2 kg	6.6 kg	
4019588855441	6585/1544	yellow with Smiley	10.2 kg	6.6 kg	87.00 x 95.00 x 24.00 cm

<b>LOCAL OSCILLATOR</b>	Colour tone: beige, polar white, slate-grey, brick-red, fir green, yellow	G/T: 17.2 dB/K
Low band: 9.75 GHz ± 3MHz	<b>INPUT FREQUENCY RANGE</b>	Gain: 38.2 dBi @11,3 GHz
High band: 10.6 GHz ± 3MHz	Low band: 10.7 ... 11.7 GHz	Offset angle: 21 °
<b>AMBIENT OPERATING CONDITIONS</b>	High band: 11.7 ... 12.75 GHz	Satellite positions: Eutelsat 13° Ost, Astra 19,2° Ost, Astra 23,5° Ost, Astra 28,2° Ost
Humidity: 5 - 100 %	<b>NOISE FACTOR</b>	Mast Ø: 65 mm max.
Ambient temperature: -40 bis 65 °C	Lower frequency range: 0.1 dB max.	Feed reception: for Skytenne-System
<b>GENERAL CHARACTERISTICS</b>	Upper frequency range: 0.1 dB max.	<b>SCOPE OF DELIVERY</b>
Top features: 1 to various receptors	<b>OUTPUT FREQUENCY RANGE</b>	Digital Satellite dish SATMAN 850 Plus, AZ/EL-mount (with corresponding multifeed-bus), 4 x Universal-Quattro-LNB, screws, installation manual
Material: Aluminium	Low band: 950 ... 1950 MHz	
Top features: 4 orbital positions	High band: 1100 ... 2150 MHz	
Top features: optimized for roof mounting	<b>POWER SUPPLY</b>	
Top features: perfect for the reception of the BBC channels on Astra & Eutelsat 28.5°	LNB voltage supply: 11 ... 20 V	
Top features: You may need various distribution components for the Mutliparticipant reception please ask you nearest TechniSat Partner	Power consumption: typ. 680 mA (4 x LNB á 170 mA)	
Material strength: 1.6 mm	<b>TECHNICAL DATA</b>	
Coating: Powder-coated on both sites	Rated measurement: 0.85 m	
	F/D: 0.67	

### KEYFEATURES

HDTV

Multiple subscribers

4 orbit positions

## Testurteil(e) SKYTENNE



Leserwahl König Kunde  
Award - 2. Platz in der  
Kategorie Sat-Anlagen  
(Camping, Cars & Caravans)