



UNYSAT Universal-Twin-LNB

Digital-LNB for two participants

EAN	Colour	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
4019588088825	grey	0000/8882	500 g	440 g	7.50 x 13.00 x 17.50 cm	10.00 x 22.00 x 19.00 cm

TOP FEATURES

Für 2 Teilnehmer

Passend für alle TechniSat SATMAN Spiegel

LOCAL OSCILLATOR

Low band : 9,75 GHz

High band : 10,6 GHz

Accuracy : ± 1 MHz

Temperature drift : ± 3 MHz

Phase noise : -75 dBc/Hz @10kHz

LNB CONTROL

Vertical : 11,5 ... 14,5 V

Horizontal : 16 ... 19 V

Band switch : 22 kHz

AMBIENT OPERATING CONDITIONS

Ambient temperature : -30 ... 60 °C

Humidity : 10 ... 90 %

INPUT FREQUENCY RANGE

Low band : 10,7 ... 11,7 GHz

High band : 11,7 ... 12,75 GHz

NOISE FACTOR

Noise figure : 0.6 dB

OUTPUT FREQUENCY RANGE

Low band : 950 ... 1950 MHz

High band : 1100 ... 2150 MHz

POWER SUPPLY

LNB voltage supply : 11.5 ... 19 V

Power consumption : max. 190 mA

PREPARED FOR

Number of orbit positions : 1

Number of clients : 2

TECHNICAL DATA

Outputs : 2

Amplification : 52 ... 65 dB

Feed reception : Für SATMAN

Impedance : 75 Ω

Connector type : F-Buchse