



TECHNIROUTER 9/2x4 G

Digital single-cable solution for two orbital positions (with PIN code technology)

EAN	Item no.	Colour	Weight (Box)	Weight	Box	Device (W x H x D)
4019588032965	0000/3296	blue/yellow	800 g	500 g	31.80 x 20.00 x 4.50 cm	29.20 x 11.20 x 3.10 cm

AMBIENT OPERATING CONDITIONS Ambient temperature: -25 ... 55 °C Humidity: 10 ... 75 %	POWER SUPPLY Frequency: 50 Hz Nominal voltage: 230 V Mains adapter: internal	Satellite inputs: 8 Terrestrial input: 1 Number of cable connections: 2 Subscribers per cable: maximal 4
AMPLIFICATION Sat: 17 ... 22 dB Terrestrial: -5 dB	RECEPTION RANGE Sat: 950 ... 2150 MHz Terrestrial: 47 ... 862 MHz	SCOPE OF DELIVERY TechniRouter 9/2x4 G, Instruction manual, power supply
DECOUPLING Trunks: 45 dB	SINGLE-CABLE OUTPUT Output frequency: 47 ... 2150 MHz Number of output channels: 2 x 4 Frequency of the output channels: 1284, 1400, 1516, 1632 MHz	
GENERAL CHARACTERISTICS Top features: Einspeisung von digitalen Sat-Signalen in vorhandene Kabelstrukturen Top features: Keine weitere Kabelverlegung erforderlich Top features: 2 Orbitpositionen ohne Einschränkung mit 2 Quatro-LNB zu empfangen Top features: Eingang zum Empfang von Terrestrischen Signalen	Frequency SAT: 950 ... 2150 MHz Frequency DVB-T: 47 ... 862 MHz	
TECHNICAL DATA		
KEYFEATURES		
HDTV	DiSEqC EN50494	2 orbit positions