



2 YEARS
WARRANTY

ENERGY
SAVER

BESSER
MADE IN
GERMANY

TECHNIROUTER 9/2x4 G

Digital single-cable solution for two orbital positions (with PIN code technology)

EAN	Colour	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
4019588032965	blue/yellow	0000/3296	800 g	500 g	29.20 x 11.20 x 3.10 cm	31.80 x 20.00 x 4.50 cm

TOP FEATURES

Einspeisung von digitalen Sat-Signalen in vorhandene Kabelstrukturen

Keine weitere Kabelverlegung erforderlich

2 Orbitpositionen ohne Einschränkung mit 2 Quatro-LNB zu empfangen

Eingang zum Empfang von Terrestrischen Signalen

AMBIENT OPERATING CONDITIONS

Humidity : 10 ... 75 %

Ambient temperature : -25 ... 55 °C

AMPLIFICATION

Sat : 17 ... 22 dB

Terrestrial : -5 dB

DECOUPLING

Trunks : 45 dB

POWER SUPPLY

Mains adapter : internal

Frequency : 50 Hz

Nominal voltage : 230 V

RECEPTION RANGE

Sat : 950 ... 2150 MHz

Terrestrial : 47 ... 862 MHz

SINGLE-CABLE OUTPUT

Output frequency : 47 ... 2150 MHz

Number of output channels : 2 x 4

Frequency of the output channels : 1284, 1400, 1516, 1632 MHz

Frequency SAT : 950 ... 2150 MHz

Frequency DVB-T : 47 ... 862 MHz

TECHNICAL DATA

Satellite inputs : 8

Terrestrial input : 1

Number of cable connections : 2

Subscribers per cable : maximal 4

SCOPE OF DELIVERY

TechniRouter 9/2x4 G, Instruction manual, power supply