



2 way satellite splitter

for the 2-fold distribution or merger of Sat signals

EAN	Item no.	Colour	Weight (Box)	Weight	Device (W x H x D)	Box
4019588032200	0000/3220	silver	50 g	50 g	5.80 x 5.20 x 2.20 cm	7.60 x 2.80 x 9.80 cm

TOP FEATURES

DC power pass

DC-diodenentkoppelt

DiSEqC-compatible

TECHNIROUTER-compatible

DECOUPLING

5 - 862 MHz : Typ. 16 dB (< 40 MHz = 8 dB)

950 - 1750 MHz : Typ. 15 dB

1750 - 2150 MHz : Typ. 12 dB

RETURN LOSS

5 - 862 MHz : Typ. 16 dB

950 - 1750 MHz : Typ. 12 dB

1750 - 2150 MHz : Typ. 12 dB

TECHNICAL DATA

Input : 1

Outputs : 2

Frequency range : 5 ... 2150 MHz

Shielding factor : ≥ 75 dB EN 50083-2 (Class A)

Connector type : F female

Impedance : 75 Ω

TRANSMISSION LOSS

5 - 862 MHz : Typ. 4 dB (± 1)

950 - 1750 MHz : Typ. 5 dB ($\pm 1,5$)

1750 - 2150 MHz : Typ. 7 dB (± 2)