



TECHNIVISION 26 ST

26 inch LCD television with integrated digital satellite and DVB-T tuner with Common Interface

EAN	Colour	Item no.	Weight (Box)	Weight	Unit without stand (W x H x D)	Device (W x H x D)	Box
4019588266445	black	5026/6404	11,5 kg	8,2 kg	660 x 450 x 100 mm	66 x 49,5 x 20,5 cm	75,5 x 58,5 x 25 cm
4019588266438	black	5026/6403	9 kg	9 kg	660 x 450 x 100 mm	66 x 49,5 x 20,5 cm	75,5 x 58,5 x 25 cm

AMBIENT OPERATING CONDITIONS	Weight without stand : 7 kg	Total programme memory : 4.000
Humidity : 10 75 %	Set height without stand : 450 mm	POWER CONSUMPTION
Ambient temperature : 5 35 °C	Set width without stand : 660 mm	Energy class : D
LNB CONTROL	DISPLAY	Standby LED : 0,53 W
Current consumption : 400 mA	Size (cm) : 66	In operation : 83 W
DiSEqC : DiSEqC 1.0 / DiSEqC 1.2 Sat Channel Router	Format : 16:9	annual energy consumption when switched on : 121 kilowatt hour per annum
Band switch : 22 kHz	Contrast ratio : 700:1	Off status : 0
Horizontal : <20 V without load, > 17.2 V at 400 mA / LNB shut-off standby mode V	Brightness : 400 cd/m²	Power switch : Yes
Vertical : <14 V without load, > 11.5 V at 400 mA V	Response time : 5 ms	POWER SUPPLY
AUDIO	Angle of view : 150° V / 160° H	Mains adapter : internal
Speakers : 2 W	Freeze frame : Yes	Frequency : 50 Hz
AC3 Dolby Digital bitstream out : Yes	Zoom : Yes	Nominal voltage : 230 V
CONNECTIONS	Type : TFT-LCD	TUNER
HDMI™ (in) : 1	Size (inches) : 26	Tuner type : DigitalSat und DVB-T-Empfangstuner
Common Interface (CI) : 2	SD : Yes	DVB-S tuner : 1
Subwoofer output : Yes	Resolution (vertical and horizontal) : 1366 x 768	DVB-T Tuner : 1
VGA : Yes	HANDLING/COMFORT	Analogue UHF/VHF/CATV tuner : 1
YUV (component input) : Yes	Sleep timer : Yes	Reception on : SD (MPEG-2)
Scart : 1	Alarm : Yes	Input impedance : 75 Ω
S Video : Yes	HOTEL MODE	TECHNIROUTER ready : Yes
Video IN : 1	Radio mode : Yes	
F socket : 1	Mixing of channel slots : Yes	
RS-232 : 0	MATERIALS CONTAINED	
DECRYPTION SYSTEM	Lead : Yes	
CI : Yes	OTHER FEATURES	
DIMENSIONS / WEIGHT	OSD languages : Czech, Polish, Hungarian, Greek, English, Dutch, Russian, German, Swedish, Spanish, Portuguese, French, Turkish, Italian	
Set depth without stand : 100 mm		

TUNER - ANALOGUE	TUNER - SAT	TUNER - TERRESTRIAL
Reception range : 46 860 MHz	DVB-S : QPSK	Reception range 2 : 470 ... 860 MHz
Video standards : PAL, SECAM	Reception range : 950 ... 2.150 MHz	Reception range 1 : 174 ... 230 MHz
	DVB-S : 1 ... 45	Voltage supply : 0,05 V
	FEC : Viterbi and Reed-Solomon	Transmission mode : 2k/8k
	Viterbi rates : 1/2, 2/3, 3/4, 5/6, 7/8	Power supply : 5 A
		Bitrate : 4 32
		Demodulation : COFDM
		WALL BRACKET
		VESA wall mounting standards : VESA 200 x 100
		SCOPE OF DELIVERY
		TechniVision 26 ST, Remote control, Power cable



The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.