



2 YEARS
WARRANTY

**BESSER
MADE IN
GERMANY**

Active 2-way tap 9/2A

Active 2-way tap for 2 orbital positions

EAN	Item no.	Colour	Weight (Box)	Weight	Device (W x H x D)	Box
4019588032330	0000/3233	silver	500 g	432 g	23.90 x 6.70 x 2.70 cm	25.20 x 7.40 x 4.60 cm

TOP FEATURES

Gleiches Rastermass der F-Buchsen wie 9er GIGASWITCH und TECHNIROUTER

AMBIENT OPERATING CONDITIONS

Ambient temperature : -25 ... 55 °C

AMPLIFICATION

Sat : 3 ... 6 dB

Terrestrial : 5 ... 10 dB einstellbar

DECOUPLING

Output : 45 dB

Trunks : 60 dB

POWER SUPPLY

Nominal voltage : 15 V

Power consumption : typ. 150 mA @15V, je Abzweigegruppe

RECEPTION RANGE

Sat : 950 ... 2150 MHz

Terrestrial : 47 ... 862 MHz

TECHNICAL DATA

Satellite inputs : 8

Terrestrial input : 1

TRANSMISSION LOSS

Sat : 0.6 ... 1 dB

Terrestrial : 1.2 dB

SCOPE OF DELIVERY

Active 2-way tap 9/2A, instruction manual