



2 YEARS
WARRANTY

**BESSER
MADE IN
GERMANY**

Active 2-way tap 17/2A

Active 2-way tap for 4 orbital positions

EAN	Item no.	Colour	Weight (Box)	Weight	Device (W x H x D)	Box
4019588032705	0000/3270	silver	858 g	800 g	21.30 x 4.30 x 10.50 cm	23.10 x 10.70 x 6.00 cm

TOP FEATURES

Gleiches Rastermass der F-Buchsen wie GIGASYSTEM 17/8

AMBIENT OPERATING CONDITIONS

Ambient temperature : -25 ... 55 °C

AMPLIFICATION

Sat : 3 ... 6 dB

Terrestrial : 5 dB einstellbar

DECOUPLING

Output : 45 dB

Trunks : 50 dB

POWER SUPPLY

Power consumption : typ. 300 mA @18V, je Abzweigegruppe

RECEPTION RANGE

Sat : 950 ... 2150 MHz

Terrestrial : 47 ... 862 MHz

TECHNICAL DATA

Satellite inputs : 16

Terrestrial input : 1

TRANSMISSION LOSS

Sat : -1.5 ... -1 dB

Terrestrial : -1.2 dB

SCOPE OF DELIVERY

Active 2-way tap 17/2A, instruction manual