



## Active 2-way tap 17/2A

Active 2-way tap for 4 orbital positions

| EAN           | Item no.  | Colour | Weight (Box) | Weight | Device (W x H x D)   | Box                |
|---------------|-----------|--------|--------------|--------|----------------------|--------------------|
| 4019588032705 | 0000/3270 | silver | 858 g        | 800 g  | 21,3 x 4,3 x 10,5 cm | 23,1 x 10,7 x 6 cm |

### TOP FEATURES

Gleiches Rastermass der F-Buchsen wie GIGASYSTEM 17/8

#### AMBIENT OPERATING CONDITIONS

Ambient temperature : -25 ... 55 °C

#### AMPLIFICATION

Sat : 3 ... 6 dB

Terrestrial : 5 dB einstellbar

#### DECOUPLING

Output : 45 dB

Trunks : 50 dB

#### POWER SUPPLY

Power consumption : typ. 300 mA @18V, je Abzweigegruppe

#### RECEPTION RANGE

Sat : 950 ... 2.150 MHz

Terrestrial : 47 ... 862 MHz

#### TECHNICAL DATA

Satellite inputs : 16

Terrestrial input : 1

#### TRANSMISSION LOSS

Sat : -1,5 ... -1 dB

Terrestrial : -1,2 dB

#### SCOPE OF DELIVERY

Active 2-way tap 17/2A, instruction manual