



Universal-Twin-LNB

Digital-TWIN-LNB for two participants

EAN	Colour	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
4019588788824	grey	0007/8882	300 g	300 g	10,1 x 7 x 12,5 cm	7,5 x 11,5 x 13 cm

LOCAL OSCILLATOR
Low band : 9,75 GHz
High band : 10,6 GHz
Accuracy : ± 1 MHz
Temperature drift : ± 3 MHz
Phase noise : -75 @10kHz
LNB CONTROL
Vertical : 11,5 ... 14 V
Horizontal : 16 ... 19 V
Band switch : 22 kHz
AMBIENT OPERATING CONDITIONS
Ambient temperature : -30 ... 60 °C
Humidity : 10 ... 90 %
INPUT FREQUENCY RANGE
Low band : 10,7 ... 11,7 GHz
High band : 11,7 ... 12,75 GHz
NOISE FACTOR
Noise figure : 0,8 dB
OUTPUT FREQUENCY RANGE
Low band : 950 ... 1.950 MHz
High band : 1.100 ... 2.150 MHz
POWER SUPPLY
LNB voltage supply : 11,5 ... 19 V
Power consumption : max. 190 mA
PREPARED FOR
Number of orbit positions : 1
Number of clients : 2
TECHNICAL DATA
Outputs : 2
Connector type : F-Buchse
Amplification : 52 ... 65 dB

Impedance : 75 Ω
 Feed reception : 40 mm