



Universal-Twin-LNB

Digital-TWIN-LNB for two participants

EAN	Colour	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
4019588788824	grey	0007/8882	300 g	300 g	10,1 x 7 x 12,5 cm	7,5 x 11,5 x 13 cm

LOCAL OSCILLATOR

Low band : 9,75 GHz

High band : 10,6 GHz

Accuracy : ± 1 MHz

Temperature drift : ± 3 MHz

Phase noise : -75 @10kHz

LNB CONTROL

Vertical : 11,5 ... 14 V

Horizontal : 16 ... 19 V

Band switch : 22 kHz

AMBIENT OPERATING CONDITIONS

Humidity : 10 ... 90 %

Ambient temperature : -30 ... 60 °C

INPUT FREQUENCY RANGE

Low band : 10,7 ... 11,7 GHz

High band : 11,7 ... 12,75 GHz

NOISE FACTOR

Noise figure : 0,8 dB

OUTPUT FREQUENCY RANGE

Low band : 950 ... 1.950 MHz

High band : 1.100 ... 2.150 MHz

POWER SUPPLY

LNB voltage supply : 11,5 ... 19 V

Power consumption : max. 190 mA

TECHNICAL DATA

Outputs : 2

Connector type : F-Buchse

Amplification : 52 ... 65 dB

Impedance : 75 Ω

Feed reception : 40 mm