



Universal-V/H-LNB

Digital-LNB for single-reception

EAN	Item no.	Colour	Weight (Box)	Weight	Device (W x H x D)	Box
4019588178946	0017/8194	grey	200 g	120 g	5.80 x 5.80 x 11.30 cm	6.50 x 6.50 x 12.00 cm

LOCAL OSCILLATOR

Low band: 9,75 GHz

High band: 10,6 GHz

LNB CONTROL

Vertical: 11.5 ... 14 V

Horizontal: 16 ... 19 V

Band switch: 22 kHz

AMBIENT OPERATING CONDITIONS

Ambient temperature: -30 ... 60 °C

Humidity: 10 ... 90 %

INPUT FREQUENCY RANGE

Low band: 10,7 ... 11,7 GHz

High band: 11,7 ... 12,75 GHz

NOISE FACTOR

Noise figure: 0.7 dB

OUTPUT FREQUENCY RANGE

Low band: 950 ... 1950 MHz

High band: 1100 ... 2150 MHz

POWER SUPPLY

LNB voltage supply: 11.5 ... 19 V

Power consumption: max. 190 mA

TECHNICAL DATA

Outputs: 1

Feed reception: 40 mm

Connector type: F-Buchse

Impedance: 75 Ω

Amplification: 50 ... 65 dB

KEYFEATURES

HDTV

1 subscriber

1 orbit position