



## Universal-V/H-LNB

Digital-LNB for single-reception

EAN	Colour	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
4019588178946	grey	0017/8194	200 g	120 g	5,8 x 5,8 x 11,3 cm	6,5 x 6,5 x 12 cm

### LOCAL OSCILLATOR

Low band : 9,75 GHz

High band : 10,6 GHz

### LNB CONTROL

Vertical : 11,5 ... 14 V

Horizontal : 16 ... 19 V

Band switch : 22 kHz

### AMBIENT OPERATING CONDITIONS

Ambient temperature : -30 ... 60 °C

Humidity : 10 ... 90 %

### INPUT FREQUENCY RANGE

Low band : 10,7 ... 11,7 GHz

High band : 11,7 ... 12,75 GHz

### NOISE FACTOR

Noise figure : 0,7 dB

### OUTPUT FREQUENCY RANGE

Low band : 950 ... 1.950 MHz

High band : 1.100 ... 2.150 MHz

### POWER SUPPLY

LNB voltage supply : 11,5 ... 19 V

Power consumption : max. 190 mA

### PREPARED FOR

Number of clients : 1

Number of orbit positions : 1

### TECHNICAL DATA

Outputs : 1

Amplification : 50 ... 65 dB

Impedance : 75 Ω

Feed reception : 40 mm

Connector type : F-Buchse