



DIGIPAL T2/C HD

EAN	Colour	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
4019588109384	anthrazit	0010/4938	790 g	240 g	18,2 x 4 x 12,6 cm	30,5 x 7,4 x 17,5 cm

TOP FEATURES

DVB-T2 HD (H.265/HEVC), DVB-T2 (H.264) or DVB-T
ISI mode: simplified device control

Electronic program guide (EPG)
Operation on 12V

Internetradiofunktion
Internet radio function

SONSTIGES

ts_mehrwert_isipro_kabel : Yes

TECHNISAT ADDED VALUE SERVICES

AUTOINSTALL : Yes

CONNECTIONS

HDMI™ (out) : 1

audio/video output analog (3.5 mm jack) :
Yes TechniSat specific adapter set
necessary (available at 0000/3649)

USB : 1 (USB 2.0)

Smartcard reader : Yes

Digital electric audio output (S/PDIF) : Yes

Ethernet 10/100 (RJ-45) : Yes

IEC-Connector : Yes

DECODER

Video decoder : MPEG-2 MP@HL/ML,
H.264/MPEG-4 AVC, H.265/HEVC

Audio decoder : MPEG-1 & MPEG-2 Layer I,
II, III

DECRYPTION SYSTEM

Irddeto : Yes

DISPLAY

Freeze frame : Yes

SD : Yes

HD : Yes

1080p : Yes

1080i : Yes

720p : Yes

576p : Yes

576i : Yes

HANDLING/COMFORT

Teletext subtitles : Yes

Media Player : Yes

Sleep timer : Yes

Teletext : Yes

Ideal for camping : Yes

Alarm : Yes

OTHER FEATURES

OSD languages : English, German, French,
Greek, Italian, Lithuanian, Dutch, Polish,
Portuguese, Spanish, Czech, Turkish,
Hungarian, Swedish

POWER CONSUMPTION

Standby LED : < 0,3 W

In operation : 4,7 W

POWER SUPPLY

Mains adapter : extern DC 12 V / 1,5 A

Nominal voltage : 230 V

Frequency : 50 Hz

READY FOR RECEPTION

freenetTV : Yes

SUPPORTED FORMATS & CODECS

Video-Formats : MKV, MP4, MOV, MPG,
MTS, TS, TS4, VOB, M2TS, AVI

Picture-Formats : BMP, JPEG, PNG, TIFF

Audio-Formats : AAC, MP3, M4A, MP2

TUNER

Tuner type : Single-Tuner

DVB-C Tuner : 1

Tuner DVB-T2 : DVB-T2/HEVC (H.265)

DVB-T Tuner : 1

Reception on : HD-TV, SD-TV, radio

TUNER - CABLE

Reception range : 47 ... 862 MHz

Demodulation : 16 / 32 / 64 / 128 / 256 QAM

Symbol rate : 1,5 ... 7,2

FEC : Reed-Solomon (204, 188)

TUNER - TERRESTRIAL

Reception range 1 : 174 ... 230 MHz

Reception range 2 : 470 ... 862 MHz

Demodulation : COFDM / QPSK, 16-QAM, 64-QAM, 256-QAM

Transmission mode : 1k, 2k, 4k, 8k, 16k, 32k

Voltage supply : 5 V

Power supply : max. 0,03 A

SCOPE OF DELIVERY

DIGIPAL T2 HD, remote control
TechniControl incl. batteries, power supply,
HDMI cable, manual



The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.