



SATMAN 65 PLUS with SCR-LNB

SATMAN external unit with pre-assembled AZ/EL mount, 65 cm Ø

EAN	Colour	Item no.	Weight (Box)	Weight
4019588888609	beige	2065/8886	8.8 kg	5.2 kg
4019588888630	slate/grey	2365/8886	8.8 kg	5.2 kg
4019588888647	brick/red	2465/8886	8.8 kg	5.2 kg
4019588888760	polar/white	2765/8886	8.8 kg	5.2 kg
4019588888654	yellow with Smiley	2565/8886	8.8 kg	5.2 kg

TOP FEATURES

For 1 participants

1 orbital position (for example Astra 19.2° East)

Ideal for wall and roof mounting

LOCAL OSCILLATOR

Low band : 9.75 GHz

High band : 10.7 GHz

LNB CONTROL

Vertical : 11,5 - 14,5 V

Horizontal : 16 - 19 V

INPUT FREQUENCY RANGE

Low band : 10.7 ... 11.7 GHz

High band : 11.7 ... 12.75 GHz

NOISE FACTOR

Lower frequency range : 0.6 dB max.

Upper frequency range : 0.6 dB max.

OUTPUT FREQUENCY RANGE

Low band : 950 ... 1950 MHz

High band : 1100 ... 2150 MHz

PREPARED FOR

Number of orbit positions : 1

Number of clients : 6

TECHNICAL DATA

Rated measurement : 0.65 m

F/D : 0.69

G/T : 14.5 dB/K

Offset angle : 27°

Gain : 35.7 dBi @11,3 GHz

Mast Ø : 65 mm max.

Feed reception : for UNYSAT-Universal-LNB

SCOPE OF DELIVERY

Satellite dish antenna SATMAN 65, AZ/EL bracket mount, SCR LNB, screws, installation instructions