



TECHNITOP HAV 30

CATV amplifier with 30/20 dB gain and return path of 5-65 MHz.

EAN	Colour	Item no.	Weight (Box)	Weight	Box	Device (W x H x D)
4019588131392	white	0001/3139	362 g	332 g	14.20 x 9.70 x 5.00 cm	13.30 x 6.70 x 3.90 cm

AMBIENT OPERATING CONDITIONS	Frequency: 50 Hz	Connector type: F female
Humidity: 10 ... 75 %	Effective output: 3,5 W	Impedance: 75 Ω
Ambient temperature: -20 ... 50 °C	RANGE OF ADJUSTMENT	Return loss: ≥ 10 dB
AMPLIFICATION	Attenuator: 0 ... 17 dB	SCOPE OF DELIVERY
Amplification: ≤ 30 dB	Equaliser: 0 ... 17 dB	TECHNITOP HAV 30; installation manual
Return path: -2.5 dB	TECHNICAL DATA	
GENERAL CHARACTERISTICS	Frequency range: 87 ... 862 MHz	
Top features: Switchable gain 20/30 dB	Frequency range return path: 5 ... 65 MHz	
Top features: Gain and slope adjustable	Amplification: 20 / 30 dB switchable	
Top features: Return channel compatible (DOCSIS)	Output level: 97 dBμV (CTB, CTO, EN 50083-3)	
POWER SUPPLY	Noise factor: ≤ 8.5 dB	
Mains adapter: internal	Shielding factor: ≥ 75 dB EN 50083-2 (Class A)	
Nominal voltage: 230 V ~	Protection class: IP 20	