




Universal Quattro-LNB

Digital LNB for multi-switch distribution

EAN	Colour	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
4019588083806	black	0000/8380	232 g	198 g	5,4 x 10,1 x 13,3 cm	10,6 x 13,8 x 6,1 cm

TOP FEATURES

For multi-switch distribution

Feed ø 40 mm

F connectors

LTE interference-safe

LOCAL OSCILLATOR

Low band : 9,75 GHz

High band : 10,6 GHz

Accuracy : ± 1 MHz

Temperature drift : ± 2,5 MHz

Phase noise : -85 @10kHz

Amplification : 60 ... 67 dB

Feed reception : 40 mm

Connector type : F female

Impedance : 75 Ω

AMBIENT OPERATING CONDITIONS

Ambient temperature : -40 ... 70 °C

Humidity : 10 ... 95 %

INPUT FREQUENCY RANGE

Low band : 10,7 ... 11,7 GHz

High band : 11,7 ... 12,75 GHz

NOISE FACTOR

Noise figure : typ. 0,75 dB

OUTPUT FREQUENCY RANGE

Low band : 950 ... 1.950 MHz

High band : 1.100 ... 2.150 MHz

POWER SUPPLY

LNB voltage supply : 11,5 ... 19 V

Power consumption : 200 mA

TECHNICAL DATA

Outputs : 4

SCOPE OF DELIVERY

Universal-Quattro-LNB