



Universal-Twin-LNB

EAN	Colour	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
4019588208827	white	0020/8882	180 g	102 g	5.40 x 5.40 x 12.30 cm	6.00 x 6.00 x 13.20 cm

TOP FEATURES

Ultra low noise

Weather protection housing

Feed ø 40 mm

LOCAL OSCILLATOR

Low band : 9,75 GHz

High band : 10,6 GHz

Accuracy : ± 1 MHz

Temperature drift : ± 0.5 MHz

Phase noise : -75 @10kHz

LNB CONTROL

Vertical : 10.5 ... 14 V

Horizontal : 16 ... 23 V

Band switch : 22 kHz

AMBIENT OPERATING CONDITIONS

Ambient temperature : -40 ... 70 °C

Humidity : 10 ... 95 %

INPUT FREQUENCY RANGE

Low band : 10,7 ... 11,7 GHz

High band : 11,7 ... 12,75 GHz

NOISE FACTOR

Noise figure : typ. 0.1 dB

OUTPUT FREQUENCY RANGE

Low band : 950 ... 1950 MHz

High band : 1100 ... 2150 MHz

POWER SUPPLY

LNB voltage supply : 10.5 ... 23 V

Power consumption : max. 140 mA

PREPARED FOR

Number of clients : 2

Number of orbit positions : 1

TECHNICAL DATA

Outputs : 2

Connector type : F female

Feed reception : 40 mm

Amplification : 58 ... 64 dB

Impedance : 75 Ω