



Universal-Twin-LNB

EAN	Colour	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
4019588208827	white	0020/8882	180 g	102 g	5,4 x 5,4 x 12,3 cm	6 x 6 x 13,2 cm

TOP FEATURES

Ultra low noise	Weather protection housing	Feed ø 40 mm
-----------------	----------------------------	--------------

LOCAL OSCILLATOR	TECHNICAL DATA
Low band : 9,75 GHz	Outputs : 2
High band : 10,6 GHz	Impedance : 75 Ω
Accuracy : ± 1 MHz	Feed reception : 40 mm
Temperature drift : ± 0,5 MHz	Connector type : F female
Phase noise : -75 @10kHz	Amplification : 58 ... 64 dB
LNB CONTROL	
Vertical : 10,5 ... 14 V	
Horizontal : 16 ... 23 V	
Band switch : 22 kHz	
AMBIENT OPERATING CONDITIONS	
Ambient temperature : -40 ... 70 °C	
Humidity : 10 ... 95 %	
INPUT FREQUENCY RANGE	
Low band : 10,7 ... 11,7 GHz	
High band : 11,7 ... 12,75 GHz	
NOISE FACTOR	
Noise figure : typ. 0,1 dB	
OUTPUT FREQUENCY RANGE	
Low band : 950 ... 1.950 MHz	
High band : 1.100 ... 2.150 MHz	
POWER SUPPLY	
LNB voltage supply : 10,5 ... 23 V	
Power consumption : max. 140 mA	