



TECHNITENNE 60 with Twin-LNB

60 cm digital satellite antenna made of steel with twin LNB

EAN	Colour	Item no.	Weight	Device (W x H x D)	Box
4019588106826	light gray	1060/2882	2.1 kg	56.00 x 65.00 x 50.00 cm	58.00 x 65.40 x 13.40 cm
4019588136823	anthracite	1360/2882	2.1 kg	56.00 x 65.00 x 50.00 cm	58.00 x 65.40 x 13.40 cm

LOCAL OSCILLATOR

Low band : 9,75 GHz

High band : 10,6 GHz

Accuracy : ± 1 MHz

Temperature drift : ± 0.5 MHz

Phase noise : -75 dBc/Hz @10kHz

LNB CONTROL

Vertical : 10.5 ... 14 V

Horizontal : 16 ... 23 V

Band switch : 22 kHz

INPUT FREQUENCY RANGE

Low band : 10,7 ... 11,7 GHz

High band : 11,7 ... 12,75 GHz

OUTPUT FREQUENCY RANGE

Low band : 950 ... 1950 MHz

High band : 1100 ... 2150 MHz

PREPARED FOR

Number of orbit positions : 1

Number of clients : 2

TECHNICAL DATA

Rated measurement : 0.56 m

F/D : 0.49

G/T : 14.5 dB/K

Gain : 35.3 dBi @11.30GHz

Offset angle : 27.77 °

Mast \varnothing : 32 ... 50 mm

Feed reception : 40 mm

Outputs : 2

Connector type : F female

Impedance : 75 Ω

Amplification : 58 ... 64 dB (LNB)