



## TECHNITENNE 60 with Twin-LNB

60 cm digital satellite antenna made of steel with twin LNB

EAN	Colour	Item no.	Weight	Device (W x H x D)	Box
4019588106826	light/gray	1060/2882	2,1 kg	56 x 65 x 50 cm	58 x 65,4 x 13,4 cm
4019588136823	anthracite	1360/2882	2,1 kg	56 x 65 x 50 cm	58 x 65,4 x 13,4 cm

### LOCAL OSCILLATOR

Low band : 9,75 GHz

High band : 10,6 GHz

Accuracy :  $\pm 1$  MHz

Temperature drift :  $\pm 0,5$  MHz

Phase noise : -75 @10kHz

### LNB CONTROL

Vertical : 10,5 ... 14 V

Horizontal : 16 ... 23 V

Band switch : 22 kHz

### GENERAL CHARACTERISTICS

Material : steel

Material strength : 0,5 mm

Coating : painted

### INPUT FREQUENCY RANGE

Low band : 10,7 ... 11,7 GHz

High band : 11,7 ... 12,75 GHz

### OUTPUT FREQUENCY RANGE

Low band : 950 ... 1.950 MHz

High band : 1.100 ... 2.150 MHz

### TECHNICAL DATA

Rated measurement : 0,56 m

F/D : 0,49

G/T : 14,5

Offset angle : 27,77 °

Gain : 35,3 dBi @11.30GHz

Mast  $\varnothing$  : 32 ... 50 mm

Feed reception : 40 mm

Outputs : 2

Connector type : F female

Impedance : 75  $\Omega$

Amplification : 58 ... 64 dB (LNB)