



UNYSAT Universal-Twin-LNB

Digital-LNB for two participants

EAN	Colour	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
4019588108820	grey	0010/8882	305 g	285 g	7,5 x 13 x 14 cm	10 x 8 x 15 cm

TOP FEATURES

For 2 participant

Special weatherproof housing for the excellent receiving electronics

Suitable for all TechniSat SATMAN dishes

Quick and easy assembly without a retaining clamp

LTE interference-safe

LOCAL OSCILLATOR

Low band : 9,75 GHz

High band : 10,6 GHz

Accuracy : ± 1 MHz

Temperature drift : $\pm 0,5$ MHz

Phase noise : -75 @10kHz

LNB CONTROL

Vertical : 10,5 ... 14 V

Horizontal : 16 ... 23 V

Band switch : 22 kHz

AMBIENT OPERATING CONDITIONS

Ambient temperature : -40 ... 70 °C

Humidity : 10 ... 95 %

INPUT FREQUENCY RANGE

Low band : 10,7 ... 11,7 GHz

High band : 11,7 ... 12,75 GHz

NOISE FACTOR

Noise figure : typ. 0,1 dB

OUTPUT FREQUENCY RANGE

Low band : 950 ... 1.950 MHz

High band : 1.100 ... 2.150 MHz

POWER SUPPLY

Power consumption : max. 140 mA

TECHNICAL DATA

Outputs : 2

Connector type : F female

Feed reception : For SATMAN

Amplification : 58 ... 64 dB

Impedance : 75 Ω