



DIGIPAL T2/C DVR

DVB-T2 HD receiver with PVR ready function

EAN	Colour	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
4019588149397	silber	0001/4939	936 g	254 g	18.20 x 4.00 x 12.60 cm	30.00 x 7.40 x 18.00 cm

TOP FEATURES

DVB-T/T2 with H.265/HEVC and H.264

Recording function via USB (DVRready)

ISI Mode: vereinfachte Gerätebedienung

ISI mode: simplified device control

Electronic program guide (EPG)

Operation on 12V

LED display

Internet radio function

MULTIMEDIA

DVR function : Ja

DVR storage medium : via USB

Timeshift : Yes

Recordings folder management : Yes

TECHNISAT ADDED VALUE SERVICES

AUTOINSTALL : Yes

ISI-Mode : Yes

CONNECTIONS

HDMI™ (out) : 1

audio/video output analog (3.5 mm jack) :
Yes TechniSat specific adapter set
necessary (available at 0000/3649)

USB : 1 (USB 2.0)

Smartcard reader : Yes

Digital electric audio output : Yes

Ethernet 10/100 (RJ-45) : Yes

IEC-Connector : Yes

DECODER

Video decoder : MPEG-2 MP@HL/ML,
H.264/MPEG-4 AVC, H.265/HEVC

Audio decoder : MPEG-1 & MPEG-2 Layer I,
II, III

DECRYPTION SYSTEM

Irdeco : Yes

DISPLAY

SD : Yes

HD : Yes

1080p : Yes

1080i : Yes

720p : Yes

576i : Yes

Type : 7 segment, 4 digits, white

HANDLING/COMFORT

Page memory : 1000

Teletext subtitles : Yes

Media Player : Yes

Ideal for camping : Yes

Sleep timer : Yes

Teletext : Yes

OTHER FEATURES

OSD languages : English, German, French,
Greek, Italian, Dutch, Polish, Portuguese,
Russian, Swedish, Spanish, Czech, Turkish,
Hungarian

Total programme memory : 5000

POWER SUPPLY

Frequency : 50 Hz

Nominal voltage : 230 V

Mains adapter : extern DC 12V/1,5A

READY FOR RECEPTION

freenetTV : Yes

SUPPORTED FORMATS & CODECS

Video-CODECS : H.264, MPEG-2, H.265

Video-Formats : MOV, MP4, MPG, TS, TS4,
M2TS, AVI, ASF

Picture-Formats : BMP, JPEG, GIF, PNG

Audio-Formats : AAC, MP3, M4A, MP2

TUNER

Tuner type : Single tuner

DVB-C Tuner : 1

DVB-T Tuner : 1

Reception on : DVB-T2 with HEVC/H.265
and H.264, DVB-T

TUNER - CABLE

Reception range : 47 ... 862 MHz

Demodulation : 16 / 32 / 64 / 128 / 256 QAM

Symbol rate : 1.5 ... 7.2

FEC : Reed-Solomon (204, 188)

TUNER - TERRESTRIAL

Reception range 1 : 174 ... 230 MHz

Reception range 2 : 470 ... 862 MHz

Demodulation : COFDM / QPSK, 16-QAM,
64-QAM, 256-QAM

Transmission mode : 1k, 2k, 4k, 8k, 16k, 32k

Voltage supply : 5 V

SCOPE OF DELIVERY

DIGIPAL T2 HD, remote control
TechniControl incl. batteries, power supply,
HDMI cable, manual



The terms HDMI, HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.