



## SKYRIDER DOME Twin

Compact, mobile DigitalSat system with twin LNB

EAN	Item no.	Weight (Box)	Weight	Box	Device (W x H x D)
4019588245808	0245/1580	7.3 kg	4.7 kg	47.70 x 54.10 x 47.70 cm	45.00 x 41.00 x 45.00 cm

<b>LOCAL OSCILLATOR</b>	Low band: 10.7 - 11.7 GHz	Outputs: 2
Low band: 9.75 GHz	High band: 11.7 - 12.75 GHz	F/D: 0.23
High band: 10.6 GHz	<b>OUTPUT FREQUENCY RANGE</b>	G/T: 9.7 dB/K
<b>LNB CONTROL</b>	Low band: 950 - 1950 MHz	Gain: 31 dBi
DiSEqC: 1.0 / 1.1	High band: 1100 - 2150 MHz	Connector type: F socket
Vertical: 10.5 ~ 14.5 V	<b>POWER CONSUMPTION</b>	<b>SCOPE OF DELIVERY</b>
Horizontal: 15.5 ~ 21 V	In operation: 30 W max. (während der Satellitensuche)	SKYRIDER Dome, instruction manual, controller, remote control, 2 x F-type SAT cable, 12 volt adapter cable
<b>AMBIENT OPERATING CONDITIONS</b>	<b>POWER SUPPLY</b>	
IP class: X 6	Nominal voltage: DC 12 ... 24 V	
Ambient temperature: -20 ... 60 °C	Power consumption: 170 mA (LNB)	
<b>GENERAL CHARACTERISTICS</b>	Effective output: 18 W / 1,5 A max.	
Material: plastic	<b>PREPARED FOR</b>	
<b>HANDLING/COMFORT</b>	Number of clients: 2	
Satellite search time: Bis zu 180 s (typisch)	Number of orbit positions: 4	
<b>INPUT FREQUENCY RANGE</b>	<b>TECHNICAL DATA</b>	

KEYFEATURES	
HDTV	Camping 2 subscribers