



## SKYRIDER 65 Twin

Automatic digital satellite reception system for camper vans/mobile homes

EAN	Colour	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
4019588255821	yellow with Smiley	2565/1582	20.25 kg	13.55 kg	67.00 x 18.50 x 98.00 cm	98.50 x 71.80 x 42.90 cm
4019588275829	polar white	2765/1582	20.25 kg	13.55 kg	67.00 x 18.50 x 98.00 cm	98.50 x 71.80 x 42.90 cm

<b>AMBIENT OPERATING CONDITIONS</b>	Effective output : 50 W / 4,2 A max.
IP class : X 6	<b>PREPARED FOR</b>
Ambient temperature : -20 ... 60 °C	Number of orbit positions : 10
<b>LOCAL OSCILLATOR</b>	Number of clients : 2
Low band : 9.75 GHz	<b>TECHNICAL DATA</b>
High band : 10.6 GHz	Outputs : 2
<b>LNB CONTROL</b>	F/D : 0.6
DiSEqC : 1.0 / 1.1	G/T : 14.5
Vertical : 10.5 ~ 14.5 V	Gain : 35.7 dBi
Horizontal : 15.5 ~ 21 V	Offset angle : 27 ° (EL 0 ~ 145° / AZ 390°)
<b>DIMENSIONS / WEIGHT</b>	Amplification : 55 ... 65 dB
Device height (retracted) : 175 mm	Connector type : F socket
Device height (extended) : 980 mm	<b>SCOPE OF DELIVERY</b>
<b>HANDLING/COMFORT</b>	Automatic control unit for SKYRIDER 65, single LNB, assembly instructions, mounting plate, controller, remote control, 2 x F-type SAT cable, 12 volt adapter cable, roof gasket
Maximum permissible speed : 130 km/h	
Satellite search time : Bis zu 180 s (typisch)	
<b>INPUT FREQUENCY RANGE</b>	
Low band : 10.7 - 11.7 GHz	
High band : 11.7 - 12.75 GHz	
<b>NOISE FACTOR</b>	
Noise figure : typ. 0.7 dB	
<b>OUTPUT FREQUENCY RANGE</b>	
Low band : 950 - 1950 MHz	
High band : 1100 - 2150 MHz	
<b>POWER CONSUMPTION</b>	
In operation : 50 W / 4 A max. (während der Satellitensuche)	
<b>POWER SUPPLY</b>	
Nominal voltage : DC 12 V	
Power consumption : 170 mA (LNB)	

Testurteil(e) SKYRIDER 65 Twin



Camping-Tipp  
SATVISION 04/20



Testnote: gut (90,8 %)  
SATVISION 04/20