



## MultyVision 40

Full-HD eLED Digital Television with Dual HDTV multituner for reception of analogue and digital TV. Integrated DVR for recording HD and standard TV and radio programmes.

EAN	Weight without stand	Item no.	Hard drive	Colour	Weight (Box)	Weight	Unit without stand (W x H x D)	Device (W x H x D)	Box
401958874 0068	17 kg	5740/0306	500 GB	silver	28 kg	20 kg	955 x 638 x 61 mm	95.50 x 69.20 x 22.00 cm	113.00 x 92.00 x 30.00 cm
401958874 0167	17 kg	5740/0316	500 GB	titanium	28 kg	20 kg	955 x 638 x 61 mm	95.50 x 69.20 x 22.00 cm	113.00 x 92.00 x 30.00 cm

### TOP FEATURES

Dual HDTV multituner for receiving DVB-S, DTT and DVB-C incl. HDTV  
Integrated DVR (500 GB hard drive) and recording

Rotating pedestal  
LED time and program display

2x Common Interface (CI+)  
UPnP (Universal Plug and Play), incl. DLNA

### AMBIENT OPERATING CONDITIONS

Humidity : 10 - 75 %

Ambient temperature : 5 - 35 °C

### LNB CONTROL

Vertical : <14 V without load, > 11.5 V at 400 mA V

Horizontal : <20 V without load, > 17.2 V at 400 mA / LNB shut-off standby mode V

DiSEqC : DiSEqC 1.0 and 1.2 / DiSEqC 1x Sat Channel Router

Band switch : 22 kHz

Current consumption : 400 mA max. kurzschlussfest 400 mA

### TECHNISAT ADDED VALUE SERVICES

AUTOINSTALL : Yes

### AUDIO

AC3 Dolby Digital bitstream out : Yes

Speakers : 2 x broadband speakers with bass reflex

### CARD READER

SD card : Yes

### CONNECTIONS

HDMI (in) : 3 (davon 1 x HDMI Mini Front)

HDMI (out) : 1

Smartcard reader : Yes (Conax)

Digital electric audio output : Yes (Adapter)

Digital optical audio out : Yes (Toslink)

Digital audio in : Yes (Adapter)

Audio out analogue : Yes (3.5mm Klinke)

AV input : Yes (Front)

Audio in/AUX in : Yes (3.5mm Klinke)

VGA : Yes

YUV (component input) : Yes (Adapter)

Scart : 1

Ethernet 10/100 (RJ-45) : Yes (RJ-45)

IEC-Connector : Yes

<b>DECRYPTION SYSTEM</b>	<b>HOTEL MODE</b>	<b>TUNER</b>
Conax : Yes	Customisable start screen : Yes	DVB-S tuner : 2
CI+ : Yes	Configurable on times : Yes	DVB-C Tuner : 2
<b>DIMENSIONS / WEIGHT</b>	Energy card function : Yes	DVB-T Tuner : 2
Set depth without stand : 61 mm	USB cloning function : Yes	Analogue UHF/VHF/CATV tuner : 2
Set height without stand : 638 mm	Multimedia connectors : Yes	TECHNIROUTER ready : Yes
Weight without stand : 17 kg	Menu locking : Yes	Reception on : HDTV (Mpeg-4+2) SD (MPEG-2)
Set width without stand : 955 mm	Integrated LED clock : Yes	Input impedance : 75 Ω
<b>DISPLAY</b>	Radio mode : Yes	<b>TUNER - ANALOGUE</b>
Size (cm) : 102 cm	Mixing of channel slots : Yes	Reception range : 47 ... 862 MHz
Frequency : 200 Hz	Multicode remote control : Yes	Video standards : B/G stereo, D/K mono, L/L, I
Format : 16:9	Fireproofed housing : Yes	<b>TUNER - CABLE</b>
Contrast ratio : 5.000:1	<b>MATERIALS CONTAINED</b>	FEC : Reed-Solomon
Picture in Picture (PIP) : Yes (2 x SD, 1 x SD u. 1 x HD)	Lead : Yes	Symbol rate : 1.7 ... 7 Mbaud
Brightness : 450 cd/m <sup>2</sup>	<b>OTHER FEATURES</b>	Reception range : 51 ... 858 MHz
Response time : 6 ms	OSD languages : Greek, Swedish, German, Hungarian, Dutch, Spanish, Italian, Portuguese, French, Turkish, Russian, English, Polish, Czech	Demodulation : 16 / 32 / 64 / 128 / 256 QAM
Angle of view : 178° / 178°	Total programme memory : 5000	<b>TUNER - SAT</b>
Picture and Picture (PAP) : Yes (2 x SD, 1 x SD u. 1 x HD)	Regional channel selection : Yes	Reception range : 950 ... 2150 MHz
Freeze frame : Yes	<b>POWER SUPPLY</b>	DVB-S : QPSK
Zoom : Yes	Nominal voltage : 230 V	DVB-S2 : QPSK - 8PSK
Resolution (vertical and horizontal) : 1920 x 1080	Frequency : 50 Hz	FEC : Viterbi and Reed-Solomon
Size (inches) : 40	Mains adapter : internal	DVB-S : 1 ... 45 Mbaud
720p : Yes	<b>SUPPORTED FORMATS &amp; CODECS</b>	Viterbi rates : 1/2, 2/3, 3/4, 5/6, 7/8
Type : Edge LED LCD	Video-Codecs : MPEG-1, MPEG-2, H.264	DVB-S2 : 10 ... 31 Mbaud
HD : Yes	Video-Formats : TS, MPG, TS4, VOB	<b>TUNER - TERRESTRIAL</b>
SD : Yes	JPEG : Yes	Demodulation : COFDM
1080i : Yes	Audio-Formats : MP2, MP3	Reception range 2 : 470 ... 860 MHz
<b>HANDLING/COMFORT</b>		Power supply : 0.03 A
Sleep timer : Yes		Voltage supply : 5 V
Clock : Yes		Bitrate : 4 ... 32
Alarm : Yes		Transmission mode : 2k/8k
		Reception range 1 : 174 ... 230 MHz
		<b>WALL BRACKET</b>
		VESA wall mounting standards : VESA 400 x 400
		<b>SCOPE OF DELIVERY</b>
		MultyVision, Pedestal, Power cable, remote control TechniControl Plus incl. batteries, Remoty Plus, Multi audio/video adapter, Cleaning set, Instruction manual