



DIGIDISH 33 with Universal-Twin-LNB

The DigiDish 33 is enormously high-performance for its size and takes up very little space

EAN	Item no.	Colour	Weight (Box)	Weight	Device (W x H x D)	Box
4019588033283	1033/2882	beige	2.8 kg	2 kg	33.00 x 35.00 cm	40.50 x 39.50 x 22.00 cm
4019588333284	1333/2882	slate/grey	2.8 kg	2 kg	33.00 x 35.00 cm	40.50 x 39.50 x 22.00 cm
4019588348820	1433/2882	brick/red	2.8 kg	2 kg	33.00 x 35.00 cm	40.50 x 39.50 x 22.00 cm
4019588733282	1733/2882	polar/white	2.8 kg	2 kg		
4019588533820	1533/2882	yellow with Smiley	2.8 kg	2 kg	33.00 x 35.00 cm	40.50 x 39.50 x 22.00 cm

TOP FEATURES

Only 33 cm small

1 or 2 participants

1 orbital position (for example Astra 19.2° East)

Especially suitable for balcony installation / Ideal for the city

Ideal for ground and wall mounting

LOCAL OSCILLATOR

Low band : 9.75 GHz

High band : 10.7 GHz

LNB CONTROL

Vertical : 11,5 - 14 V

Horizontal : 16 - 19 V

Band switch : 22 kHz

INPUT FREQUENCY RANGE

Low band : 10.7 ... 11.7 GHz

High band : 11.7 ... 12.75 GHz

NOISE FACTOR

Lower frequency range : 0.7 dB max.

Upper frequency range : 0.7 dB max.

OUTPUT FREQUENCY RANGE

Low band : 950 - 1950 MHz

High band : 1100 - 2150 MHz

POWER SUPPLY

LNB voltage supply : 11.5 ... 19 V

Power consumption : max. 190 mA

PREPARED FOR

Number of orbit positions : 1

Number of clients : 2

TECHNICAL DATA

Rated measurement : 0.33 m

F/D : 0.6

Gain : 30 dBi @11,3 GHz

Offset angle : 30°

Feed reception : 40 mm

SCOPE OF DELIVERY

Satellite dish 33 cm, LNB, Wall bracket, Screws, Tool, Mounting instruction

Universal-Twin-LNB

ARTICLE INFORMATION	LNB CONTROL	High band : 1100 ... 2150 MHz
EAN : 4019588788824	Vertical : 11.5 ... 14 V	POWER SUPPLY
Colour : grey	Horizontal : 16 ... 19 V	LNB voltage supply : 11.5 ... 19 V
Item no. : 0007/8882	Band switch : 22 kHz	Power consumption : max. 190 mA
Weight (Box) : 300 g	AMBIENT OPERATING CONDITIONS	PREPARED FOR
Weight : 300 g	Ambient temperature : -30 ... 60 °C	Number of orbit positions : 1
Device (W x H x D) : 10.10 x 7.00 x 12.50 cm	Humidity : 10 ... 90 %	Number of clients : 2
Box : 7.50 x 11.50 x 13.00 cm	INPUT FREQUENCY RANGE	TECHNICAL DATA
LOCAL OSCILLATOR	Low band : 10,7 ... 11,7 GHz	Outputs : 2
Low band : 9,75 GHz	High band : 11,7 ... 12,75 GHz	Connector type : F-Buchse
High band : 10,6 GHz	NOISE FACTOR	Amplification : 52 ... 65 dB
Accuracy : \pm 1 MHz	Noise figure : 0.8 dB	Impedance : 75 Ω
Temperature drift : \pm 3 MHz	OUTPUT FREQUENCY RANGE	Feed reception : 40 mm
Phase noise : -75 @10kHz	Low band : 950 ... 1950 MHz	

Testurteil(e) DIGIDISH 33 with Universal-Twin-LNB



Readers' Choice for the König-Kunde-Award 2014:
2nd place in the satellite equipment category
(Camping, Cars & Caravans)

black/white