



## DIGIDISH 45 with Universal-Twin-LNB

Thanks to its ingenious reflector design the reception performance of the DigiDish 45 is better than with many 60 cm mirrors - and that is with a far lower size of reflector.

EAN	Item no.	Colour	Weight (Box)	Weight	Device (W x H x D)	Box
4019588452824	1045/2882	beige	3.7 kg	2.9 kg	45.00 x 48.00 cm	51.00 x 51.00 x 23.00 cm
4019588453821	1345/2882	slate/grey	3.7 kg	2.9 kg	45.00 x 48.00 cm	51.00 x 51.00 x 23.00 cm
4019588448827	1445/2882	brick/red	3.7 kg	2.9 kg	45.00 x 48.00 cm	51.00 x 51.00 x 23.00 cm
4019588478824	1745/2882	polar/white			45.00 x 48.00 cm	51.00 x 51.00 x 23.00 cm
4019588542822	1545/2882	yellow with Smiley	3.7 kg	2.9 kg		

### TOP FEATURES

Only 45 cm small  
1 or 2 participants

1 orbital position (for example Astra 19.2° East)

Ideal for ground and wall mounting

Especially suitable for balcony installation / Ideal for the city

Also available as a complete package including digital satellite receiver

#### LOCAL OSCILLATOR

Low band : 9.75 GHz

High band : 10.7 GHz

#### LNB CONTROL

#### Universal-Twin-LNB

Horizontal : 16 - 19 V

#### BAND SWITCH : 22 kHz ARTICLE INFORMATION INPUT FREQUENCY RANGE

Low band : 10.7 ... 11.7 GHz

High band : 11.7 ... 12.75 GHz

#### NOISE FACTOR

Lower frequency range : 0.7 dB max.

Upper frequency range : 0.7 dB max.

#### OUTPUT FREQUENCY RANGE

Low band : 950 - 1950 MHz

High band : 1100 - 2150 MHz

#### POWER SUPPLY

LNB voltage supply : 11.5 ... 19 V

Power consumption : max. 190 mA

#### PREPARED FOR

Number of orbit positions : 1

Number of clients : 2

#### TECHNICAL DATA

Rated measurement : 0.45 m

F/D : 0.6

Offset angle : 30°

Gain : 32.2 dBi @11,3 GHz

Feed reception : 40 mm

#### SCOPE OF DELIVERY

Satellite dish 45 cm, LNB, wall bracket, screws, tool, mounting instruction

## Testurteil(e) DIGIDISH 45 with Universal-Twin-LNB



Zweiter Platz in der Kategorie Sat-Anlagen bei der Leserwahl zum König-Kunde-Award 2014 (Camping, Cars & Caravans)